



**GROZ**

**INDUSTRIAL PRODUCT  
CATALOGUE JULY 2024**



	CAT NR.	DESCRIPTION / SIZE	MOQ.
<b>STRIKING TOOLS</b>			
<b>NEW!</b>			
	<b>INDESTRUCTIBLE HANDLE CLUB HAMMERS</b>		
	<b>HEAVY DUTY 52 HRC HEAD</b>		
	CHID/2.5/12	Head weight : 1.1 Kg (2.5 lbs) Handle length : 12" (300 mm)	8
	CHID/4/12	Head weight : 1.8 Kg (4 lbs) Handle length : 12" (300 mm)	8
	CHID/4/16	Head weight : 1.8 Kg (4 lbs) Handle length : 16" (400 mm)	8
	<b>SOFT FACE 30 HRC HEAD</b>		
	CHID/SF/2.5/12	Head weight : 1.1 Kg (2.5 lbs) Handle length : 12" (300 mm)	8
	CHID/SF/4/12	Head weight : 1.8 Kg (4 lbs) Handle length : 12" (300 mm)	8
	<b>INDESTRUCTIBLE HANDLE SLEDGE HAMMERS</b>		
	<b>HEAVY DUTY 52 HRC HEAD</b>		
	SHID/6/24	Head weight : 2.7 Kg (6 lbs) Handle length : 24" (600 mm)	4
	SHID/6/30	Head weight : 2.7 Kg (6 lbs) Handle length : 30" (750 mm)	4
	SHID/8/24	Head weight : 3.6 Kg (8 lbs) Handle length : 24" (600 mm)	4
	SHID/8/30	Head weight : 3.6 Kg (8 lbs) Handle length : 30" (750 mm)	4
	SHID/8/36	Head weight : 3.6 Kg (8 lbs) Handle length : 36" (900 mm)	4
	SHID/10/30	Head weight : 4.5 Kg (10 lbs) Handle length : 30" (750 mm)	4
	SHID/12/30	Head weight : 5.5 Kg (12 lbs) Handle length : 30" (750 mm)	4
	SHID/14/30	Head weight : 6.3 Kg (14 lbs) Handle length : 30" (750 mm)	4
	SHID/20/36	Head weight : 9 Kg (20 lbs) Handle length : 36" (900 mm)	2
	<b>SOFT FACE 30 HRC HEAD</b>		
	SHID/SF/6/30	Head weight : 2.7 Kg (6 lbs) Handle length : 30" (750 mm)	4
	SHID/SF/8/30	Head weight : 3.6 Kg (8 lbs) Handle length : 30" (750 mm)	4
	SHID/SF/10/30	Head weight : 4.5 Kg (10 lbs) Handle length : 30" (750 mm)	4
	SHID/SF/12/30	Head weight : 5.5 Kg (12 lbs) Handle length : 30" (750 mm)	4
	SHID/SF/14/36	Head weight : 6.3 Kg (14 lbs) Handle length : 36" (900 mm)	4

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>INDESTRUCTIBLE HANDLE COPPER HEAD SLEDGE HAMMERS</b>		
	CHID/2.5/12/CU	Head weight : 1.1 Kg (2.5 lbs) Handle length : 12" (300 mm)	4
	CHID/2.5/16/CU	Head weight : 1.1 Kg (2.5 lbs) Handle length : 16" (400 mm)	4
	CHID/4/12/CU	Head weight : 1.8 Kg (4 lbs) Handle length : 12" (300 mm)	4
	CHID/4/16/CU	Head weight : 1.8 Kg (4 lbs) Handle length : 16" (400 mm)	4
	SHID/8/24/CU	Head weight : 3.6 Kg (8 lbs) Handle length : 24" (600 mm)	2
	SHID/14/30/CU	Head weight : 6.3 Kg (14 lbs) Handle length : 30" (750 mm)	2
	<b>INDESTRUCTIBLE HANDLE BRASS HEAD SLEDGE HAMMER</b>		
	SHID/2.5/12/BR	Head weight : 1.1 Kg (2.5 lbs) Handle length : 12" (300 mm)	4
	SHID/4/12/BR	Head weight : 1.8 Kg (4 lbs) Handle length : 12" (300 mm)	4
	SHID/4/16/BR	Head weight : 1.8 Kg (4 lbs) Handle length : 16" (400 mm)	4
	SHID/6/30/BR	Head weight : 2.7 Kg (6 lbs) Handle length : 30" (762 mm)	2
	SHID/8/30/BR	Head weight : 3.6 Kg (8 lbs) Handle length : 30" (762 mm)	2
	<b>INDESTRUCTIBLE HANDLE BALL PEIN HAMMERS</b>		
	<b>HEAVY DUTY 52 HRC HEAD</b>		
	BPID/16/14	Head weight : 0.450 Kg (16 oz.) Handle length : 14" (350 mm)	8
	BPID/20/14	Head weight : 0.565 Kg (20 oz.) Handle length : 14" (350 mm)	8
	BPID/24/14	Head weight : 0.680 Kg (24 oz.) Handle length : 14" (350 mm)	8
	BPID/32/14	Head weight : 0.900 Kg (32 oz.) Handle length : 14" (350 mm)	8
	BPID/48/14	Head weight : 1.360 Kg (48 oz.) Handle length : 14" (350 mm)	8
	<b>SOFT FACE 30 HRC HEAD</b>		
	BPID/SF/24/14	Head weight : 0.680 Kg (24 oz.) Handle length : 14" (350 mm)	8
	<b>INDESTRUCTIBLE HANDLE CROSS PEIN HAMMERS</b>		
	CPID/2/16	Head weight : 1.1 Kg (2.5 lbs) Handle length : 16" (400 mm)	8
	CPID/3/16	Head weight : 1.6 Kg (3.5 lbs) Handle length : 16" (400 mm)	8
	<b>INDESTRUCTIBLE HANDLE CLAW HAMMERS</b>		
	CLID/16/13	Head weight : 0.450 Kg (16 oz.) Handle length : 13" (330 mm)	12
	<b>DOUBLE FACE PLASTIC MALLET</b>		
	HMR/SF/25	Multi-purpose striking tool used for light hammering applications, fitted with plastic & rubber head	8
	KIT/HMR/SF/4ST	Mallet fitted with plastic & rubber head. Copper & brass head available as spares	8
	HD/PR/HMR/25	Red plastic head	10
	HD/BR/HMR/25	Brass head	10
	HD/CU/HMR/25	Copper head	10

	CAT NR.	DESCRIPTION / SIZE	MOQ.
<b>IMPACT &amp; RATCHET WRENCHES</b>			
	<b>3/8" IMPACT WRENCH</b>		
	IPW/201	Body Type : Aluminium Max Torque : 360 Nm Net Weight : 1.35 Kg Hammer Mechanism : Jumbo Max. Nut Capacity : M11	1
	<b>1/2" IMPACT WRENCH</b>		
	IPW/301	Body Type : Aluminium Max Torque : 1223 Nm Net Weight : 2.56 Kg Hammer Mechanism : Twin Max. Nut Capacity : M16	1
	<b>3/4" IMPACT WRENCH</b>		
	IPW/401	Body Type : Aluminium Max Torque : 2522 Nm Net Weight : 4.75 Kg Hammer Mechanism : Improved Twin Max. Nut Capacity : M24	1
	<b>1" D-HANDLE IMPACT WRENCH</b>		
	IPW/501	Body Type : Aluminium Max Torque : 2522 Nm Net Weight : 12.06 Kg Hammer Mechanism : Pinless clutch Max. Nut Capacity : M38	1
<b>TOOL STORAGE &amp; ASSORTMENTS</b>			
	<b>PORTABLE WORKSTATIONS</b>		
	MTB/7	27" Portable Workstation 7 Drawers Trolley Load Capacity : 450 Kg Drawer Load Capacity : 45 Kg	1
	<b>UNIVERSAL TOOL KIT - 149 PIECE</b>		
	MTB/7/149/AU	149 Pc tool assortment in MTB 7	1
	<b>AUTOMOTIVE TOOL KIT - 84 PIECE</b>		
	MTB/7/84/AU	84 Pc tool assortment in MTB 7	1
	<b>AUTOMOTIVE TOOL KIT - 65 PIECE</b>		
	MTB/7/65/AU	65 Pc tool assortment in MTB 7	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>5 TRAY CANTILEVER TOOL BOX</b>		
	MTB/5T	5 tray cantilever tool box with Trolley Dim. : 440 x 200 x 200 mm Load Capacity : 35 Kg	1
	BDL/MTB/5	Spare Trolley for MTB/5 Tool Box	1
	<b>5 TRAY CANTILEVER TOOL BOX WITH TOOLS</b>		
	MTB/5/64/AU	64 pcs tools assortment for use in automotive workshops & service stations	1
	MTB/5/84/AU	84 pcs tools assortment for use in automotive workshops & service stations	1


## TORQUE TOOLS

	<b>RATCHETING TORQUE WRENCHES - PRO+SERIES</b> Chrome Molybdenum alloy square drive Accuracy: ± 4% of reading. Set Torque value both in Nm & Ft. lb.		
	TQW/RT/3-8/25	Square Drive : 3/8" Torque Range : 5-25 Nm	1
	TQW/RT/3-8/50	Square Drive : 3/8" Torque Range : 10-50 Nm	1
	TQW/RT/1-2/100	Square Drive : 1/2" Torque Range : 20-100 Nm	1
	TQW/RT/1-2/200	Square Drive : 1/2" Torque Range : 40-200 Nm	1
	TQW/RT/1-2/340	Square Drive : 1/2" Torque Range : 60-340 Nm	1
	TQW/RT/3-4/750	Square drive : 3/4" Torque range : 150-750 Nm	1
	TQW/RT/0-1/1000	Square drive : 1" Torque range : 200-1000 Nm	1
	<b>RATCHETING TORQUE WRENCHES - PRO SERIES</b> Chrome Molybdenum alloy square drive Accuracy: ± 4% of reading. Set Torque value both in Nm & Ft. lb.		
	<b>NEW!</b>		
	<b>DIN 6789</b> <b>ASME B107</b>		
	TQ/20/3-8/140	Square Drive : 3/8" Torque Range : 20.3-142.4 Nm	1
TQ/30/1-2/200	Square Drive : 1/2" Torque Range : 40-200 Nm	1	
TQ/30/1-2/340	Square Drive : 1/2" Torque Range : 60-340 Nm	1	
	<b>ALUMINIUM TORQUE WRENCHES</b> 50% Lighter yet robust aluminium construction Chrome Molybdenum alloy square drive; Length independent The torque value remains within an accuracy of ± 3%		
	<b>DIN 6789</b> <b>50% LIGHTER</b> <b>ASME B107.300-2010</b>		
	TQW/AL/3-4/760	Square drive : 3/4" Torque range : 140-760 Nm	1
TQW/AL/0-1/2000	Square drive : 3/4" Torque range : 750-2000 Nm	1	

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>CLASSIC TORQUE WRENCHES</b> Solid Steel Construction Accuracy: ± 4% of reading. Complete with Calibration Certificate		
	TQW/CL/3-8/33	Square Drive : 3/8" Torque Range : 5-33 Nm	1
	TQW/CL/3-8/68	Square Drive : 3/8" Torque Range : 5-68 Nm	1
	TQW/CL/1-2/135	Square Drive : 1/2" Torque Range : 25-135 Nm	1
	TQW/CL/1-2/225	Square Drive : 1/2" Torque Range : 50-225 Nm	1
	TQW/CL/1-2/330	Square Drive : 1/2" Torque Range : 70-330 Nm	1
	TQW/CL/3-4/800	Square Drive : 3/4" Torque Range : 200-800 Nm	1
	TQW/CL/0-1/1000	Square Drive : 1" Torque Range : 200-1000 Nm	1
	<b>TORQUE MULTIPLIERS</b>		
	TQM/A/1-2/3-4/15	Torque Ratio : 1:6.5 Max Torque : 1500 Nm	1
	TQM/A/3-4/0-1/30	Torque Ratio : 1:6.5 Max Torque : 3000 Nm	1

#### AUTOMOTIVE TOOLS & ACCESSORIES

	<b>STRAP WRENCH</b>		
	STW/12G	Aluminium I-beam handle with non-marring nylon belt Handle Length: 12" (300 mm) For objects with dia: 7" (175mm)	10
	STW/18G	Aluminium I-beam handle with non-marring nylon belt Handle Length: 18" (450 mm) For objects with dia: 7" (175mm)	10
	<b>BEARING PULLERS</b> <b>2 JAW BEARING PULLERS</b> Forged Chrome Vanadium Jaws		
	BPL/2J/3	Max. Reach : 75 mm Safe Working Load : 2 Ton	1
	BPL/2J/4	Max. Reach : 100 mm Safe Working Load : 4 Ton	1
	BPL/2J/6	Max. Reach : 150 mm Safe Working Load : 6 Ton	1
	BPL/2J/8	Max. Reach : 200 mm Safe Working Load : 10 Ton	1
	<b>3 JAW BEARING PULLERS</b> Forged Chrome Vanadium Jaws		
	BPL/3J/3	Max. Reach : 75 mm Safe Working Load : 3 Ton	1
	BPL/3J/4	Max. Reach : 100 mm Safe Working Load : 6 Ton	1
	BPL/3J/6	Max. Reach : 150 mm Safe Working Load : 9 Ton	1
	BPL/3J/8	Max. Reach : 200 mm Safe Working Load : 15 Ton	1
	<b>RATCHETING BEARING PULLERS</b> Forged Chrome Molybdenum Jaws Easily Convert from 3 Jaw to 2 Jaw		
	BPL/RT/2T	Max. Reach : 80 mm Safe Working Load : 2 Ton	1
	BPL/RT/5T	Max. Reach : 150 mm Safe Working Load : 5 Ton	1
	BPL/RT/7T	Max. Reach : 218 mm Safe Working Load : 7 Ton	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>BOTTLE JACKS</b> Welded construction for leak-proof performance 50% safety overload factor Forged Steel base for better stability Comes with 'Load Limiting Device'		
	JACK/BT/12W	Capacity : 12 Ton Lift Range : 230-465 mm	1
	JACK/BT/20W	Capacity : 20 Ton Lift Range : 240-450 mm	1
	JACK/BT/32W	Capacity : 32 Ton Lift Range : 260-420 mm	1
	JACK/BT/50W	Capacity : 50 Ton Lift Range : 280-450 mm	1
	<b>FLOOR JACK</b> Heavy duty steel body with 2 piece steel handle Quick jump start to reach lifting point Built in safety valve protect against overloading		
	JACK/FL/3D	Capacity : 3 Ton Lift Range : 133-465 mm Weight : 33 Kg	1
	<b>TELESCOPIC WHEEL WRENCH</b>		<b>NEW!</b>
	WW/TP/17-23/ST	Designed to loosen out and remove wheel nuts Telescopic handle extends from 14" (350 mm) to 22" (550 mm) Comes with two 1/2" square drive dual side sockets, 17x19 mm & 21x23 mm	12
 	<b>MAGNETIC TOOL HOLDER</b>		<b>NEW!</b>
	MTH/12S/ST2	12" Tool Holder Set Of 2 Dim. : 26 x 300 mm No. of magnets : 5	5
	MTH/24S/ST2	24" Tool Holder Set Of 2 Dim. : 26 x 600 mm No. of magnets : 11	11
<b>SCREWDRIVERS &amp; HEX KEYS</b>			
	<b>7 PC VDE SCREWDRIVER SET</b> Suitable for live wire working		
	SCDR/VDE/7/ST	Slotted: 6.5 x 150 mm, 5.5 x 125mm, 4 x 100mm, 3 x 100mm Phillip: PH1 x 80mm, PH2 x 100mm Voltage Tester: VT 110-250	5

	CAT NR.	DESCRIPTION / SIZE	MOQ.
<b>HEXAGON KEY SETS</b>			
	<b>S2 STEEL CONSTRUCTION</b> Hardness : 50 - 52 HRC		<b>S2</b> <b>DIN 896</b>
	ALN/HX-BL/7L/GRZ	7 pc Set, Long - Ball End Metric: 2.5 mm - 10 mm	10
	ALN/HX-BL/7L/SAE/GRZ	7 pcs Set Long - Ball End Imperial: 3/32" - 3/8"	10
	ALN/HX-BL/9EL/GRZ	9 pcs Set Extra Long - Ball End Metric: 1.5 mm - 10 mm	10
	ALN/TX-TX/9L/GRZ	9 pcs Set Long - Torx Star T10 - T50	10
	<b>CHROME VANADIUM CONSTRUCTION</b> Hardness : 50 - 52 HRC		<b>CV</b> <b>DIN 896</b> CHROME VANADIUM
	ALN/HX-HX/8/GRZ	8 pcs Hex Key Set Metric : 1.5 mm - 6 mm	10
	ALN/HX-HX/10/GRZ	10 pcs Hex Key Set Metric : 1.5 mm - 10 mm	10
	ALN/HX-HX/10/SAE/GRZ	10 pcs Hex Key Set Imperial : 1/16" - 3/8"	10
		ALN/HX-HX/25/GRZ	25 pcs Hex Key Set - Metric & Imperial 13 pcs Metric : 1.5 mm - 10 mm 12 pcs Imperial : 1/16" - 3/8"

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	ALN/HX-HX/7/GRZ	7 pcs Hex Key Set Metric : 2.5 mm - 10 mm	10
	ALN/TX-TX/8/GRZ	8 Pc Tamper Torx Key Set T9 - T40	10

### SPANNERS & WRENCHES

	<b>REVERSIBLE RATCHETING COMBINATION SPANNERS</b> 72 teeth with 5° action arc for smooth movement Ratcheting ring feature for increase working speed, eliminating the need to remove spanner after each turn  		
	CSP/RRT/8/UG	8 mm	5
	CSP/RRT/10/UG	10 mm	5
	CSP/RRT/12/UG	12 mm	5
	CSP/RRT/13/UG	13 mm	5
	CSP/RRT/14/UG	14 mm	5
	CSP/RRT/17/UG	17 mm	5
	CSP/RRT/19/UG	19 mm	5
CSS/RRT/7ST/UG	7 pcs Spanners Set, Size: 8, 10, 12, 13, 14, 17, 19 mm	1	
	<b>DOUBLE OPEN END SPANNERS</b> Chrome Vanadium construction Hardness : 44 - 48 HRC  		
	DOSP/SF/6-7/S	6 × 7 mm	10
	DOSP/SF/8-9/S	8 × 9 mm	10
	DOSP/SF/10-11/S	10 × 11 mm	10
	DOSP/SF/12-13/S	12 × 13 mm	10
	DOSP/SF/14-15/S	14 × 15 mm	10
	DOSP/SF/16-17/S	16 × 17 mm	10
	DOSP/SF/18-19/S	18 × 19 mm	10
	DOSP/SF/20-22/S	20 × 22 mm	10
	DOSP/SF/21-23/S	21 × 23 mm	10
	DOSP/SF/24-27/S	24 × 27 mm	10
	DOSP/SF/25-28/S	25 × 28 mm	10
DOSP/SF/30-32/S	30 × 32 mm	10	
DOSS/SF/12/ST	12 pc Metric Set: 6 × 7, 8 × 9, 10 × 11, 12 × 13, 14 × 15, 16 × 17, 18 × 19, 20 × 22, 21 × 23, 24 × 27, 25 × 28, 30 × 32 mm	1	
	<b>RING SPANNERS</b> Chrome Vanadium construction Hardness : 42 - 48 HRC  		
	RSP/SF/6-7/S	6 × 7 mm	10
	RSP/SF/8-9/S	8 × 9 mm	10
	RSP/SF/10-11/S	10 × 11 mm	10
	RSP/SF/12-13/S	12 × 13 mm	10
	RSP/SF/14-15/S	14 × 15 mm	10
	RSP/SF/16-17/S	16 × 17 mm	10
	RSP/SF/18-19/S	18 × 19 mm	10
RSP/SF/20-22/S	20 × 22 mm	10	

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	RSP/SF/21-23/S	21 × 23 mm	10
	RSP/SF/24-27/S	24 × 27 mm	10
	RSP/SF/25-28/S	25 × 28 mm	10
	RSP/SF/30-32/S	30 × 32 mm	10
	RSS/SF/12/ST	12 pc Metric Set: 6 × 7, 8 × 9, 10 × 11, 12 × 13, 14 × 15, 16 × 17, 18 × 19, 20 × 22, 21 × 23, 24 × 27, 25 × 28, 30 × 32 mm	1

## PLIERS & CUTTERS

	<b>INSULATION PLIERS</b> Chrome Vanadium construction Hardness : 35 - 50 HRC			
	<b>COMBINATION PLIERS</b>			
	CPL/CV/6#1	Length : 6"		12
	CPL/CV/7#1	Length : 7"		12
	CPL/CV/8 #1	Length : 8"		12
	<b>LONG NOSE PLIERS</b>			
	LNP/CV/6 #1	Length : 6"	12	
	LNP/CV/7#1	Length : 7"	12	
	<b>SIDE CUTTING PLIERS</b>			
	SCP/CV/6 #1	Length : 6"	12	
	<b>CIRCLIP PLIERS</b> Chrome Vanadium construction Hardness : 40 - 45 HRC			
	CLP/ST/E/150	Length: 150 mm, External Straight	12	
	CLP/ST/E/175	Length: 175 mm, External Straight	12	
	CLP/ST/I/150	Length: 150 mm, Internal Straight	12	
	CLP/ST/I/175	Length: 175 mm, Internal Straight	12	
	CLP/BND/E/150	Length: 150 mm, External Bent	12	
	CLP/BND/E/175	Length: 175 mm, External Bent	12	
	CLP/BND/I/150	Length: 150 mm, Internal Bent	12	
	CLP/BND/I/175	Length: 175 mm, Internal Bent	12	
	<b>ADJUSTABLE WRENCHES</b> Chrome Vanadium construction Hardness : 38 - 46 HRC			
	AWR/CV/6	Length: 6" (150 mm)	12	
	AWR/CV/8	Length: 8" (200 mm)	10	
	AWR/CV/10	Length: 10" (250 mm)	10	
	AWR/CV/12	Length: 12" (300 mm)	10	

## HACKSAW FRAMES

	<b>SUPER CUT HI-TENSION HACKSAW</b>	
	HF/40/BL	30,000 PSI Tension Hacksaw frame Aluminium die cast handle, adjustable for 10" & 12" blades. Comes with 12" (300 mm) bi-metal blade

	CAT NR.	DESCRIPTION / SIZE	MOQ.
--	---------	--------------------	------

## VICES & CLAMPS

	<b>BENCH VICES - FIXED BASE</b>			
	BV/F/75	Jaw width : 75 mm Jaw opening : 100 mm Net wt. : 5.5 Kg		4
	BV/F/100	Jaw width : 100 mm Jaw opening : 125 mm Net wt. : 9.7 Kg		3
	BV/F/125	Jaw width : 125 mm Jaw opening : 150 mm Net wt. : 14.7 Kg		2
	BV/F/150	Jaw width : 150 mm Jaw opening : 175 mm Net wt. : 18.2 Kg		1
	BV/F/200	Jaw width : 200 mm Jaw opening : 200 mm Net wt. : 30.40 Kg		1
	<b>MULTI PURPOSE VICE</b>		<b>NEW!</b>	
	BV/MP/125	Jaw width : 125 mm Jaw opening : 125 mm Net wt. : 15.5 Kg	1	

## SOCKETS & SOCKET ACCESSORIES

### HAND SOCKETS

Chrome Vanadium construction with rust-proof and scratch-proof Ultra Premium finish  
'Super Grip' profile: For firm grip with enhanced engagement and transmission of higher torque  
Knurled band for non-slip grip



	<b>1/4" HEX SOCKETS</b>			
	SKT/H/1-4/4/UG	4 mm		10
	SKT/H/1-4/4.5/UG	4.5 mm		10
	SKT/H/1-4/5/UG	5 mm		10
	SKT/H/1-4/5.5/UG	5.5 mm		10
	SKT/H/1-4/6/UG	6 mm		10
	SKT/H/1-4/7/UG	7 mm		10
	SKT/H/1-4/8/UG	8 mm		10
	SKT/H/1-4/9/UG	9 mm		10
	SKT/H/1-4/10/UG	10 mm		10
	SKT/H/1-4/11/UG	11 mm		10
	SKT/H/1-4/12/UG	12 mm		10
	SKT/H/1-4/13/UG	13 mm		10
	SKT/H/1-4/14/UG	14 mm		10
	<b>1/4" HEX SOCKETS - DEEP</b>			
	SKT/H/1-4/5D/UG	5 mm		10
	SKT/H/1-4/6D/UG	6 mm		10
	SKT/H/1-4/7D/UG	7 mm		10
	SKT/H/1-4/8D/UG	8 mm		10
	SKT/H/1-4/9D/UG	9 mm		10
	SKT/H/1-4/10D/UG	10 mm		10
	SKT/H/1-4/11D/UG	11 mm		10
	SKT/H/1-4/12D/UG	12 mm		10
SKT/H/1-4/13D/UG	13 mm	10		

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>1/4" POZI BIT SOCKETS</b> 		
	SKT/1-4/PZ1/UG	PZ1	10
	SKT/1-4/PZ2/UG	PZ2	10
	SKT/1-4/PZ3/UG	PZ3	10
	<b>1/4" HEX BIT SOCKETS</b> 		
	SKT/1-4/H3/UG	H3	10
	SKT/1-4/H4/UG	H4	10
	SKT/1-4/H5/UG	H5	10
	SKT/1-4/H6/UG	H6	10
	SKT/1-4/H7/UG	H7	10
	SKT/1-4/H8/UG	H8	10
	SKT/1-4/H10/UG	H10	10
	<b>1/4" TORX BIT SOCKETS</b> 		
	SKT/1-4/T8/UG	T8	10
	SKT/1-4/T10/UG	T10	10
	SKT/1-4/T15/UG	T15	10
	SKT/1-4/T20/UG	T20	10
	SKT/1-4/T25/UG	T25	10
	SKT/1-4/T27/UG	T27	10
	SKT/1-4/T30/UG	T30	10
	SKT/1-4/T40/UG	T40	10
	<b>1/4" SLOTTED BIT SOCKETS</b> 		
	SKT/1-4/S4/UG	4 mm	10
	SKT/1-4/S5.5/UG	5.5 mm	10
	SKT/1-4/S7/UG	7 mm	10
	<b>1/4" PHILLIPS BIT SOCKETS</b> 		
	SKT/1-4/PH1/UG	PH1	10
	SKT/1-4/PH2/UG	PH2	10
	SKT/1-4/PH3/UG	PH3	10
	<b>3/8" HEX SOCKETS</b> 		
	SKT/H/3-8/6/UG	6 mm	15
	SKT/H/3-8/7/UG	7 mm	15
	SKT/H/3-8/8/UG	8 mm	15
	SKT/H/3-8/9/UG	9 mm	15
	SKT/H/3-8/10/UG	10 mm	15
	SKT/H/3-8/11/UG	11 mm	15
	SKT/H/3-8/12/UG	12 mm	15
	SKT/H/3-8/13/UG	13 mm	15
	SKT/H/3-8/14/UG	14 mm	15
	SKT/H/3-8/15/UG	15 mm	12
	SKT/H/3-8/16/UG	16 mm	12
	SKT/H/3-8/17/UG	17 mm	10
SKT/H/3-8/18/UG	18 mm	10	

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	SKT/H/3-8/19/UG	19 mm	10
	SKT/H/3-8/20/UG	20 mm	8
	SKT/H/3-8/21/UG	21 mm	8
	SKT/H/3-8/22/UG	22 mm	6
	<b>1/2" HEX SOCKETS</b> 		
	SKT/H/1-2/8/UG	8 mm	15
	SKT/H/1-2/9/UG	9 mm	15
	SKT/H/1-2/10/UG	10 mm	15
	SKT/H/1-2/11/UG	11 mm	15
	SKT/H/1-2/12/UG	12 mm	15
	SKT/H/1-2/13/UG	13 mm	15
	SKT/H/1-2/14/UG	14 mm	15
	SKT/H/1-2/15/UG	15 mm	12
	SKT/H/1-2/16/UG	16 mm	12
	SKT/H/1-2/17/UG	17 mm	10
	SKT/H/1-2/18/UG	18 mm	10
	SKT/H/1-2/19/UG	19 mm	10
	SKT/H/1-2/20/UG	20 mm	8
	SKT/H/1-2/21/UG	21 mm	6
	SKT/H/1-2/22/UG	22 mm	6
	SKT/H/1-2/23/UG	23 mm	6
	SKT/H/1-2/24/UG	24 mm	6
	SKT/H/1-2/25/UG	25 mm	6
	SKT/H/1-2/26/UG	26 mm	4
	SKT/H/1-2/27/UG	27 mm	4
	SKT/H/1-2/28/UG	28 mm	4
	SKT/H/1-2/29/UG	29 mm	4
	SKT/H/1-2/30/UG	30 mm	4
	SKT/H/1-2/32/UG	32 mm	4
	SKT/H/1-2/33/UG	33 mm	2
	SKT/H/1-2/36/UG	36 mm	2
		<b>1/2" HEX SOCKETS - DEEP</b> 	
SKT/H/1-2/10D/UG		10 mm	15
SKT/H/1-2/11D/UG		11 mm	15
SKT/H/1-2/12D/UG		12 mm	15
SKT/H/1-2/13D/UG		13 mm	15
SKT/H/1-2/14D/UG		14 mm	15
SKT/H/1-2/15D/UG		15 mm	12
SKT/H/1-2/16D/UG		16 mm	12
SKT/H/1-2/17D/UG		17 mm	10
SKT/H/1-2/18D/UG		18 mm	10
SKT/H/1-2/19D/UG		19 mm	10
SKT/H/1-2/20D/UG		20 mm	8
SKT/H/1-2/21D/UG		21 mm	8
SKT/H/1-2/22D/UG		22 mm	6
SKT/H/1-2/23D/UG		23 mm	6
SKT/H/1-2/24D/UG		24 mm	6
SKT/H/1-2/26D/UG		26 mm	6
SKT/H/1-2/27D/UG	27 mm	6	

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	SKT/H/1-2/28D/UG	28 mm	4
	SKT/H/1-2/29D/UG	29 mm	4
	SKT/H/1-2/30D/UG	30 mm	4
	SKT/H/1-2/32D/UG	32 mm	4
	<b>3/4" HEX SOCKETS</b> 		
	SKT/H/3-4/22/MT	22 mm	6
	SKT/H/3-4/24/MT	24 mm	6
	SKT/H/3-4/27/MT	27 mm	6
	SKT/H/3-4/28/MT	28 mm	6
	SKT/H/3-4/30/MT	30 mm	4
	SKT/H/3-4/32/MT	32 mm	4
	SKT/H/3-4/36/MT	36 mm	4
	SKT/H/3-4/38/MT	38 mm	4
	SKT/H/3-4/41/MT	41 mm	4
	SKT/H/3-4/46/MT	46 mm	4
	SKT/H/3-4/50/MT	50 mm	2
	<b>1" HEX SOCKETS</b> 		
	SKT/H/0-1/36/MT	36 mm	4
	SKT/H/0-1/41/MT	41 mm	4
	SKT/H/0-1/46/MT	46 mm	4
	SKT/H/0-1/50/MT	50 mm	2
	SKT/H/0-1/55/MT	55 mm	2
	SKT/H/0-1/60/MT	60 mm	2
	SKT/H/0-1/65/MT	65 mm	1
	SKT/H/0-1/70/MT	70 mm	1
	SKT/H/0-1/75/MT	75 mm	1
	SKT/H/0-1/80/MT	80 mm	1

#### SOCKET ACCESSORIES

	<b>SLIDING T BARS</b>		
	SLTB/1-4/UG	1/4" Drive, Length: 4-1/2" (115 mm)	10
	SLTB/3-8/UG	3/8" Drive, Length: 6-1/2" (165 mm)	10
	SLTB/1-2/UG	1/2" Drive, Length: 10" (250 mm)	5
	SLTB/3-4/MT	3/4" Drive, Length: 18" (450 mm)	1
	SLTB/0-1/MT	1" Drive, Length: 22" (550 mm)	1
	<b>EXTENSION BARS</b>		
	DRXB/1-4/2/UG	1/4" Drive, Length: 2" (50 mm)	10
	DRXB/1-4/4/UG	1/4" Drive, Length: 4" (100 mm)	10
	DRXB/1-4/6/UG	3/8" Drive, Length: 6" (150 mm)	10
	DRXB/3-8/3/UG	3/8" Drive, Length: 3" (75 mm)	5
	DRXB/3-8/6/UG	3/8" Drive, Length: 6" (150 mm)	5
	DRXB/1-2/5/UG	1/2" Drive, Length: 5" (125 mm)	5
	DRXB/1-2/10/UG	1/2" Drive, Length: 10" (250 mm)	5
	DRXB/3-4/4/MT	3/4" Drive, Length: 4" (100 mm)	10
	DRXB/3-4/8/MT	3/4" Drive, Length: 8" (200 mm)	5
	DRXB/0-1/8/MT	1" Drive, Length: 8" (200 mm)	5
DRXB/0-1/16/MT	1" Drive, Length: 16" (400 mm)	2	

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>UNIVERSAL JOINTS</b>		
	UVJ/1-4/UG	1/4" Drive	10
	UVJ/3-8/UG	3/8" Drive	5
	UVJ/1-2/UG	1/2" Drive	5
	UVJ/3-4/UG	3/4" Drive	5
	<b>SPEEDER HANDLE</b>		
	SPDH/1-2/UG	1/2" Drive	5
	<b>ADAPTORS</b>		
	SADP/1-4F/3-8M/UG	1/4" (F) to 3/8" (M)	5
	SADP/3-8F/1-4M/UG	3/8" (F) to 1/4" (M)	5
	SADP/3-8F/1-2M/UG	3/8" (F) to 1/2" (M)	5
	SADP/1-2F/3-8M/UG	1/2" (F) to 3/8" (M)	5
	SADP/1-2F/3-4M/UG	1/2" (F) to 3/4" (M)	5
	SADP/3-4F/1-2M/UG	3/4" (F) to 1/2" (M)	5
	SADP/3-4F/0-1M/UG	3/4" (F) to 1" (M)	2
	<b>1/2" HEX SPARK PLUG SOCKETS</b>		
	SKT/1-2/SP/16/UG	16 mm	5
	SKT/1-2/SP/21/UG	21 mm	5
	<b>L HANDLE</b>		
	LDH/1-2/UG	1/2" Drive, Length: 5" (125 mm)	5
	<b>SPINNER HANDLE</b>		
	DRSH/1-4/UG	1/4" Drive	10
	<b>FLEXIBLE EXTENSION</b>		
	FLEX/1-4/UG	1/4" Drive	10
<b>RATCHET HANDLES</b>			
	<b>SLIM LINE RATCHET HANDLES</b> 30% slimmer & lighter than any regular ratchet handle; Quick-release button replaces sockets quickly with a push of a button		
	RTD/SL/1-4/UG	1/4" Drive, Torque: 80 Nm	5
	RTD/SL/3-8/UG	3/8" Drive, Torque: 270 Nm	5
	RTD/SL/1-2/UG	1/2" Drive, Torque: 670 Nm	5
	<b>ROUND HEAD RATCHET HANDLE</b> Classic round head design Spring loaded ball attaches onto sockets, preventing them from dropping		
	RTD/RH/3-4/MT	3/4" Drive, Torque: 1412 Nm	1



	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>PEAR HEAD RATCHET HANDLE</b> Classic pear head design for strength, durability and higher performance  		
	RTD/PH/3-4/MT	3/4" Drive, Torque: 2000 Nm	1
	RTD/PH/0-1/MT	1" Drive, Torque: 2515 Nm	1
<b>SOCKET SETS IN METAL CASES</b>			
	<b>3/4" HEX SOCKET SET - 14 PCS</b> 		
	KIT/SKT/H/3-4/14/MT	Constituents 10 pcs : 3/4" Hex Sockets: 22, 24, 27, 30, 32, 36, 38, 41, 46, 50 mm 1 pc : 3/4" Drive Round Head Ratchet Handle 2 pcs : 3/4" Extension Bar: 4" (100 mm), 8" (200 mm) 1 pc : 3/4" Sliding T Bar	1
	<b>1" HEX SOCKET SET - 14 PCS</b> 		
	KIT/SKT/H/0-1/14/MT	Constituents 10 pcs : 1" Hex Sockets: 36, 41, 46, 50, 55, 60, 65, 70, 75, 80 mm 1 pc : 1" Ratchet Handle 2 pcs : 1" Extension: 8" (200 mm), 16" (400 mm) 1 pc : 1" Sliding T Bar	1
<b>HAND SOCKET SETS IN BLOW MOULDED CASES</b>			
	<b>1/4" HEX SOCKET SET - 19 PCS</b> 		
	KIT/SKT/H/1-4/19/UG	Constituents 13 pcs : 1/4" Hex Sockets: 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13, 14 mm 1 pc : 1/4" Ratchet Handle 2 pcs : 1/4" Extension Bar: 2" (50 mm), 4" (100 mm) 1 pc : 1/4" Universal Joint 1 pc : 1/4" Sliding T Bar 1 pc : 1/4" Spinner Handle	10
	<b>1/4" HEX SOCKET SET - 42 PCS</b> 		
	KIT/SKT/H/1-4/42/UG	Constituents 13 pcs : 1/4" Hex Sockets: 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13, 14 mm 6 pcs : 1/4" Hex Bit Socket: 3, 4, 5, 6, 7, 8 mm 3 pcs : 1/4" Slotted Bit Socket: 4, 5.5, 7 mm 3 pcs : 1/4" Phillips Bit Socket: PH1, PH2, PH3 3 pcs : 1/4" Pozi Bit Socket: PZ1, PZ2, PZ3 7 pcs : 1/4" Torx Bit Socket: T8, T10, T15, T20, T25, T30, T40 2 pc : 1/4" Extension Bar: 2" (50 mm), 4" (100 mm) 1 pc : 1/4" Spinner Handle 1 pc : 1/4" Flexible Extension 1 pc : 1/4" Universal Joint 1 pc : 1/4" Sliding T Bar 1 pc : 1/4" Ratchet Handle	10

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>1/4" HEX SOCKET SET - 46 PCS</b>		<b>NEW!</b> 
	KIT/HSK/1-4/46	Constituents 13 pcs : Hex Sockets : 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13 & 14 mm 6 pcs : Hex Bit Socket: 3, 4, 5, 6, 7 & 8 mm 3 pcs : Slotted Bit Socket: 44, 5.5 & 7 mm 3 pcs : Philips Bit Socket: PH1, PH2 & PH3 3 pcs : Pozidriv Bit Socket: PZ1, PZ2 & PZ3 7 pcs : Torx Bit Socket: T8, T10, T15, T20, T25, T30 & T40 4 pcs : Hex Keys 1 pc : Ratchet Handle 2 pc : Extension Bar: 2" (50 mm), 4" (100 mm) 1 pc : Universal Joint 1 pc : Sliding T Bar 1 pc : Spinner Handle 1 pc : Flexible Extension	5
	<b>1/2" HEX SOCKET SET - 13 PCS</b>		
	KIT/SKT/H/1-2/13/UG	Constituents 11 pcs : 1/2" Hex Sockets: 8, 9, 10, 11, 12, 13, 14, 15, 17, 19, 22 mm 1 pc : 1/2" Ratchet Handle 1 pc : 1/2" Extension Bar: 5" (125 mm)	5
	<b>1/2" HEX SOCKET SET - 25 PCS</b>		<b>NEW!</b> 
	KIT/HSK/1-2/25	Constituents 18 pcs : Hex Sockets: 8, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 24, 27, 30 & 32 mm 2 pcs : Spark Plug Sockets: 5/8" (16 mm), 13/16" (21 mm) 2 pc : Extension Bar: 5" (125 mm), 10" (250 mm) 1 pc : Universal Joint 1 pc : Sliding T-Bar 1 pc : Ratchet Handle	5
	<b>1/2" HEX SOCKET SET - 27 PCS</b>		
	KIT/SKT/H/1-2/27/UG	Constituents 22 pcs : 1/2" Hex Sockets: 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 21, 22, 23, 24, 26, 27, 28, 29, 30, 32 mm 2 pcs : 1/2" Extension Bar: 5" (125 mm), 10" (250 mm) 1 pc : 1/2" Universal Joint 1 pc : 1/2" Sliding T-Bar 1 pc : 1/2" Ratchet Handle	5

	CAT NR.	DESCRIPTION / SIZE	MOQ.
<b>HAND SOCKET SETS ON RAILS</b>			
	<b>1/4" HEX SOCKET SET - 9 PCS</b> 		
	KIT/SKT/H/1-4/9LH/UG	Constituents 8 pcs : 1/4" Hex Sockets: 4, 4.5, 5, 5.5, 6, 7, 8, 10 mm 1 pc : 1/4" Ratchet Handle	5
	<b>1/4" HEX SOCKET SET - 13 PCS</b> 		
	KIT/SKT/H/1-4/13L/UG	Constituents 13 pcs : 1/4" Hex Sockets: 4, 4.5, 5, 5.5, 6, 7, 8, 9, 10, 11, 12, 13, 14 mm	5
	<b>3/8" HEX SOCKET SET - 8 PCS</b> 		
	KIT/SKT/H/3-8/8L/UG	Constituents 8 pcs : 3/8" Hex Sockets: 6, 8, 10, 12, 13, 14, 17, 19 mm	5
	<b>3/8" HEX SOCKET SET - 9 PCS</b> 		
	KIT/SKT/H/3-8/9LH/UG	Constituents 8 pcs : 3/8" Hex Sockets: 6, 8, 10, 12, 13, 14, 17, 19 mm 1 pc : 3/8" Ratchet Handle	5
	<b>1/2" HEX SOCKET SET - 9 PCS</b> 		
	KIT/SKT/H/1-2/9L/UG	Constituents 9 pcs : 1/2" Hex Sockets: 9, 10, 12, 13, 14, 17, 19, 22 mm	5
	<b>1/2" HEX SOCKET SET - 11 PCS</b> 		
	KIT/SKT/H/1-2/11LH/UG	Constituents 10 pcs : 1/2" Hex Sockets: 8, 9, 10, 12, 13, 14, 17, 19, 22, 24 mm 1 pc : 1/2" Ratchet Handle	5
	<b>1/2" SPLINE BIT SOCKET SET - 6 PCS</b> 		
	KIT/BIT-SKT/SPL/1-2/6/UG	Constituents 6 pcs : 1/2" Spline Bit Sockets 55 mm length: M6, M8, M10 100 mm length: M8, M10, M12	5

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>1/2" HEX BIT SOCKET SET - 8 PCS</b>		
	KIT/BIT-SKT/H/1-2/8/UG	Constituents 8 pcs : 1/2" Hex Bit Sockets: 5, 6, 7, 8, 10, 12, 14, 17 mm	5
	<b>1/2" TORX BIT SOCKET SET - 9 PCS</b>		
	KIT/BIT-SKT/TX/1-2/9/UG	Constituents 9 pcs : 1/2" Torx Bit Sockets: T20, T25, T27, T30, T40, T45, T50, T55, T60	5

### IMPACT SOCKETS - HEX

Chrome Molybdenum Construction

Pin hole facilitates use with impact tools with pin & ring retaining mechanism

	<b>1/2" HEX IMPACT SOCKETS</b>		
	ISKT/H/1-2/10	10 mm	15
	ISKT/H/1-2/11	11 mm	15
	ISKT/H/1-2/12	12 mm	15
	ISKT/H/1-2/13	13 mm	15
	ISKT/H/1-2/14	14 mm	15
	ISKT/H/1-2/15	15 mm	12
	ISKT/H/1-2/16	16 mm	12
	ISKT/H/1-2/17	17 mm	10
	ISKT/H/1-2/18	18 mm	10
	ISKT/H/1-2/19	19 mm	10
	ISKT/H/1-2/21	21 mm	8
	ISKT/H/1-2/24	24 mm	6
	ISKT/H/1-2/27	27 mm	6
	<b>1/2" HEX IMPACT SOCKETS - DEEP</b>		
	ISKT/H/1-2/14D	14 mm	15
	ISKT/H/1-2/17D	17 mm	10
	ISKT/H/1-2/18D	18 mm	10
	ISKT/H/1-2/19D	19 mm	10
	ISKT/H/1-2/20D	20 mm	8
	ISKT/H/1-2/21D	21 mm	8
	ISKT/H/1-2/23D	23 mm	6
ISKT/H/1-2/24D	24 mm	6	

	CAT NR.	DESCRIPTION / SIZE	MOQ.	
	<b>3/4" HEX IMPACT SOCKETS</b>			
				
		ISKT/H/3-4/17	17 mm	10
		ISKT/H/3-4/19	19 mm	8
		ISKT/H/3-4/21	21 mm	6
		ISKT/H/3-4/22	22 mm	6
		ISKT/H/3-4/24	24 mm	6
		ISKT/H/3-4/27	27 mm	6
		ISKT/H/3-4/28	28 mm	6
		ISKT/H/3-4/29	29 mm	4
		ISKT/H/3-4/30	30 mm	4
		ISKT/H/3-4/33	33 mm	4
		ISKT/H/3-4/35	35 mm	4
		ISKT/H/3-4/36	36 mm	4
		ISKT/H/3-4/38	38 mm	4
	ISKT/H/3-4/41	41 mm	4	
	ISKT/H/3-4/46	46 mm	2	
	<b>3/4" HEX IMPACT SOCKETS - DEEP</b>			
				
		ISKT/H/3-4/24D	24 mm	4
		ISKT/H/3-4/27D	27 mm	4
	ISKT/H/3-4/28D	28 mm	4	
	<b>1" HEX IMPACT SOCKETS</b>			
				
		ISKT/H/0-1/19	19 mm	8
		ISKT/H/0-1/22	22 mm	6
		ISKT/H/0-1/24	24 mm	6
		ISKT/H/0-1/26	26 mm	6
		ISKT/H/0-1/27	27 mm	6
		ISKT/H/0-1/29	29 mm	4
		ISKT/H/0-1/30	30 mm	4
		ISKT/H/0-1/32	32 mm	4
		ISKT/H/0-1/33	33 mm	4
		ISKT/H/0-1/35	35 mm	4
		ISKT/H/0-1/36	36 mm	4
		ISKT/H/0-1/38	38 mm	4
		ISKT/H/0-1/41	41 mm	4
		ISKT/H/0-1/46	46 mm	4
		ISKT/H/0-1/50	50 mm	2
		ISKT/H/0-1/55	55 mm	2
	ISKT/H/0-1/60	60 mm	1	
	ISKT/H/0-1/65	65 mm	1	
	<b>1" HEX IMPACT SOCKET - DEEP</b>			
				
		ISKT/H/0-1/27D	27 mm	4
		ISKT/H/0-1/30D	30 mm	2
		ISKT/H/0-1/32D	32 mm	2
	ISKT/H/0-1/33D	33 mm	2	

## LED WORKLIGHTS

	CAT NR.	DESCRIPTION / SIZE	MOQ.
<b>WORK LIGHTS</b>			
	<b>HEAVY DUTY RECHARGEABLE COB WORKLIGHT</b> Powerful rechargeable COB worklight designed for the professional user Impact resistant		
	LED/550	10W COB Lumens:1000 Power Source: 3.7V, 4400mAh Li-ion Battery Comes with Micro USB charging cable	1
	LED/560	20W COB Lumens:2000 Power Source: 7.4V, 4400 mAh Li-ion Battery Comes with Micro USB charging cable	1
	<b>30W COB RECHARGEABLE WORKLIGHT</b> Universal dual power worklight for endless applications both indoors & outdoors 		
	LED/670	Lumens: 2800 Dual Power Source Rechargeable - 7.4V 4400 mAh Li-ion Battery AC Powered - 115V AC, 60Hz/220V AC, 50Hz	1
	LED/670T	Worklight mounted on tripod Lumens: 2800 Dual Power Source Rechargeable - 7.4V 4400 mAh Li-ion Battery AC Powered- 115V AC, 60Hz / 220V AC, 50Hz	1
	<b>CABLE REEL WORKLIGHT</b> Protected against dust and effects of water spray from any direction Impact-proof aluminium die cast housing with polycarbonate lens will stand-up to tough jobsite conditions 		
	LED/800/EU	Lumen: 4000 Power Source: 220V AC, 50HZ	1
	<b>AC POWERED SITE LAMP</b> Powerful 28 SMD portable light for use on construction sites, workshop etc.  		
	LED/602/EU	Lumen: 2100 Power Source: 220V AC, 50HZ	1
	<b>TRIPOD SITE LAMP</b> Telescopic stand can be extended from 0.8m - 1.72m (31 - 67 inch) to light overhead work or minimise shadows when casting light downwards Complete with 4m (13') long power cord  		
	LED/612/EU	Lumen: 4200 Power Source: 220V AC, 50HZ	2

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>18W LED RECHARGEABLE WORKLIGHT</b> 18W LED Worklight 6 powerful LED's of 3W each		 
	LED/621	Lumens: 1000 Power Source: 3.7V 6600 mAh Rechargeable Li-Ion Battery Heavy duty magnetic base	1
	<b>FOLDING WORKLIGHT</b> Heads can be used separately or both together for all-around illumination Nylon handle swivels full 360° for adjustment as needed Handle also doubles up as a stand for convenient placement on a flat surface Single push-button controlled output		<b>NEW!</b> 
	LED/385	Lumen: 1000 Power Source: 4 x AA Drycell Batteries	1
	<b>MAGNETIC BASE FOLDING WORKLIGHT</b> Heads can be used separately or both together for all-around illumination Nylon handle swivels full 360° for adjustment as needed Handle also doubles up as a stand for convenient placement on a flat surface Single push-button controlled output		<b>NEW!</b> 
	LED/385 RM	Lumen: 1000 Power Source: 3.7V 5000 mAh Lithium polymer battery Heavy duty magnetic base	1
	<b>HANDS FREE MULTI-FUNCTIONAL WORKLIGHT</b> 360° rotating hook to suspend light leaving both hands free Integrated pocket/belt clip to conveniently store and carry light wherever you go		<b>NEW!</b> 
	LED/390	Lumens: 150 Power Source: 3.7V 1200 mAh Rechargeable Li-Ion Battery Heavy duty magnetic base	1
	<b>360° SWIVEL RECHARGEABLE WORKLIGHT</b> Multi-function, powerful worklight & spotlight in one IK07		
	LED/360	Lumen: 400 Power Source: 7.4 V, 4400 mAh Li-ion Battery 8 hours run time at 120 lumen	1
	<b>INTENSITY CONTROL WORKLIGHT</b> 5W COB mainlight 3W Led top torch		<b>NEW!</b> 
	LED/395	Lumens: 350 Power Source: 3.7V 2000 mAh Rechargeable Li-Ion Battery Heavy duty magnetic base	1
	<b>INTENSITY CONTROL &amp; BATTERY DISPLAY WORKLIGHT</b> 10W COB worklight 3W Led top torch		<b>NEW!</b> 
	LED/396	Lumens: 500 Power Source: 3.7V 2000 mAh Rechargeable Li-Ion Battery Heavy duty magnetic base	1
	<b>UV &amp; DUAL CHARGING WORKLIGHT</b> 10W COB worklight 3W UV light		 
	LED/376U	Lumen: 550 Power Source: 3.7V 2000 mAh Rechargeable and Removable Li-Ion Battery	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>SLIM FOLDING WORKLIGHT</b> 4W COB worklight 2W SMD spotlight 0.5W SMD top torch with magnetic pick-up		<b>NEW!</b>  400
	LED/185	Lumen: 400 Power Source: 3.7V, 2600 mAh Li-ion Battery Super strong magnet on base help affix the light on any metallic surface leaving both hands free	1
	<b>FLEXIBLE INSPECTION LIGHT</b> Dual head worklight 5W COB on each side use both together or separately as needed Heavy-duty flexible neck can be rotated & bent 360° horizontally & vertically Strong magnet on base for direct attachment on any metallic surface		<b>NEW!</b>  1000
	LED/186	Lumen: 1000 Power Source: 3.7V, 2600 mAh Li-ion Battery, Type C fast charging Super strong magnet on base help affix the light on any metallic surface leaving both hands free	1
	<b>7W COB RECHARGEABLE WORKLIGHT</b> Inspection worklight with super strong magnet		 650
	LED/345	Lumen: 650 Power Source: 3.7V, 4400 mAh Li-ion Battery Aluminium tubing with TPR casing makes it impact resistant	1
	<b>MAGNETIC ENDS UNDERHOOD LIGHT</b> 10W COB slim & compact single button, user controlled light output 360° swivelling hooks resist wear and provide a scratch-proof grip		<b>NEW!</b>  1000
	LED/355	Lumens: 1000 Power Source: 7.4V 2600 mAh Rechargeable Li-Ion Battery Heavy duty magnetic ends	1
	<b>15W COB UNDER-HOOD LIGHT</b> Super bright underhood light for powerful illumination of engine bay		 1000
	LED/351	Lumen: 1000 Power Source: 3.7V, 5200 mAh Li-ion Battery, USB Chargeable Aluminium construction 3 fully adjustable light bulbs that can be used in any combination	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
<b>FLASHLIGHTS</b>			
	<b>3W COB POCKET FLASHLIGHT</b> 3W COB LED handy pocket light		
	LED/140	Lumen: 150 Power Source: 3 x AAA Alkaline Batteries	1
	<b>3W COB RECHARGEABLE PEN LIGHT</b> Super bright, dual function portable worklight & top torch		
	LED/335	Lumen: 180 Power Source: 3.7V, 800 mAh Li-ion Battery Adjustable Pocket Clip	1
	<b>3W LED SLIM PEN LIGHT</b> Extra-ordinary, high quality slim pen light designed for the professional user		
	LED/160	Lumen: 150 Power Source: 2 x AAA Battery	1
	<b>UV &amp; LASER PENLIGHT</b> 5W COB mainlight 4W LED Spotlight UV light (365nm) Laser Pointer		  <b>NEW!</b>
	LED/175	Lumen: 450 Power Source: 3.7V 800 mAh Li-Ion Battery Type C charging	1
	<b>7W LED WATERPROOF SPOTLIGHT</b> 7W LED hand held spotlight with 400m distance		 
	LED/402	Lumen: 700 Power Source: 3.7V, 2200 mAh Li-ion Battery, DC Car Charger Water Proof Spotlight	1
<b>HEADLAMPS</b>			
	<b>RECHARGEABLE HEADLAMP</b> 3W COB In-built sensor with hands free ON/OFF Detachable Design: Light can be separated from head band and used as a worklight		 <b>NEW!</b>
	LED/220	Lumen: 150 Power Source: 3.7V, 2200 mAh Li-ion Battery Ergonomic Construction	1
	<b>DUAL MODE &amp; HAND SENSOR HEADLAMP</b> 3W COB Floodlight 3W LED spotlight		 <b>NEW!</b>
	LED/225	Lumen: 500 Power Source: 3.7V, 1000 mAh Lithium polymer battery (included) 3 x AAA Drycell Batteries (not included)	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>STRIP LIGHT WITH HAND SENSOR HEADLAMP</b> 5W COB wide angle Floodlight 3W LED spotlight		<b>NEW!</b> 
	LED/250	Lumen: 350 Power Source: 3.7V, 1200 mAh Lithium polymer battery Type C fast charging	1
<b>FLOODLIGHTS</b>			
	<b>12W LED FLOODLIGHT</b> 12W LED Floodlight 4 Powerful LED's of 3W each		   
	LED/505	Lumens : 840 Power Source : 10V DC - 30V DC, 12W	1
	<b>15W LED FLOODLIGHT</b> 15W LED Floodlight 5 powerful LED's of 3W each		   
	LED/501	Lumens : 900 Power Source : 12V DC - 36V DC, 15W	1
	LED/502	Set of 2 Lumens : 900 Power Source : 110V DC - 30V DC, 15W	1
	<b>15W COMPACT LED FLOODLIGHT</b> 15W LED Floodlight 5 powerful LED's of 3W each		<b>NEW!</b>    
	LED/501S	Lumens : 1000 Power Source : 10V DC - 30V DC, 15W	1
	<b>15W LED 'SUPER COOL' FLOODLIGHT</b> 15W LED Floodlight 5 powerful LED's of 3W each		   
	LED/520	Lumens : 1050 Power Source : 12 V - 60V DC, 15W	1
	<b>18W LED 'SUPER COOL' FLOODLIGHT</b> 18W LED Floodlight 6 powerful LED's of 3W each		   
	LED/530	Lumens : 1200 Power Source : 12 V- 60V DC, 18W	1
	<b>27W LED FLOODLIGHT</b> High output, super bright illumination over long distances 9 powerful LED's of 3W each		   
	LED/512	Lumens : 1890 Power Source : 9V DC - 32 DC, 27W	1
	<b>30W LED FLOODLIGHT</b> 30W LED Floodlight 6 powerful LED's of 5W each		   
	LED/545	Lumens : 2250 Lumens Power Source : 9V DC - 32V DC, 30 W	1
	<b>45W LED FLOODLIGHT</b> 45W LED Floodlight 15 powerful LED's of 3W each		   
	LED/541	Lumens : 2150 Power Source : 9V DC - 32V DC, 45W	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>48W LED FLOODLIGHT</b> 48W LED Floodlight 16 powerful LED's of 3 W each	   	
	LED/515	Lumens : 3360 Power Source : 9V DC - 32V DC, 48W	1
<b>LED LIGHT BARS - COMBINATION BEAM (SPOT LIGHT+FLOOD LIGHT)</b>			
	<b>36W LED LIGHT BAR</b> 8" wide	 	
	LED/701	Lumen: 2520 Power Source: 10V DC - 30V DC, 36W	1
	<b>72W LED LIGHT BAR</b> 14" wide	 	
	LED/711	Lumen: 5040 Power Source: 10V DC - 30V DC, 72W	1
	<b>120W LED LIGHT BAR</b> 22" wide	 	
	LED/721	Lumen: 8400 Power Source: 10V DC - 30V DC, 120W	1
<b>FLUID HANDLING EQUIPMENT</b>			
	<b>THE ULTIMATE GREASE GUN</b>		
	K45R/B	Pressure : Upto 10,000 PSI Delivers : 1.5 gm/stroke 650 gm barrel capacity, 150 mm rigid extension & 3 jaw coupler	16
	<b>LEVER GREASE GUN - HEAVY DUTY</b>		
	G1R/HD/B	Pressure : Upto 10,000 PSI Delivers : Upto 1 gm/stroke Complete with 150 mm rigid steel extension & 4 jaw coupler	16
	<b>LEVER GREASE GUN - DUAL PISTON</b>		<b>NEW!</b>
	G2R/B	Pressure : Upto 6,000 PSI Delivers : Upto 2.4 gm/stroke  150 mm bent steel extension and coupler	16
	<b>LEVER GREASE GUN - HEAVY DUTY</b>		
	V1R/HD/CP/B 	Pressure : Upto 6,000 PSI Delivers : Upto 1 gm/stroke Finish : Zinc Plated Complete with 150 mm rigid steel extension & 4 jaw coupler	16
	<b>LEVER GREASE GUN - HEAVY DUTY</b>		
	V1R/HD/BL/B 	Pressure : Upto 6,000 PSI Delivers : Upto 1 gm/stroke Finish : Powder Coated Complete with 150 mm rigid steel extension & 4 jaw coupler	16
	<b>PISTOL GRIP GREASE GUN</b>		
	G5R/B	Pressure : Upto 5,000 PSI Delivers : Upto 0.5 gm/stroke Complete with 100 mm rigid steel extension & 4 jaw coupler	16

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>AIR OPERATED GREASE GUN</b>		<b>NEW!</b>
	AGG/1R/B	Pressure : Upto 4,800 PSI Delivers : Upto 4 gm/stroke Complete with 150 mm rigid steel extension & 4 jaw coupler	4
	<b>BATTERY POWERED GREASE GUN</b>		
	BPGG/19L1/EU	Pressure : Upto 6,000 PSI Delivers : Upto 85 gm/min 14 oz. Grease Gun 1 pc Li-Ion battery, EU Plug	3
	<b>20V CORDLESS GREASE GUN</b>		<b>NEW!</b>
	CGG/20L1/EU	Pressure : Upto 10,000 PSI Delivers : Upto 85 gm/min 1pc Li-ion battery, EU plug	1
	<b>USB RECHARGEABLE BATTERY GREASE GUN</b>		<b>NEW!</b>
	RGG/12L	Pressure : Upto 8,000 PSI Delivers : Upto 85 gm/min Charge Time : 1.5 Hrs. 2000 mAh Lithium-Ion battery powers the 12V motor with Type C charging cable 30" (750 mm) High Pressure Hose with Spring Guard with 3 Jaw Hydraulic Coupler	1
	<b>QUICK LOCK GREASE COUPLER</b>		<b>NEW!</b>
	HC/21/BSP	Conveniently engage & dis-engage under pressure 8,000 PSI	50
	<b>HYDRAULIC COUPLER - PROFESSIONAL</b>		
	HC/14/3/B	3 Jaw coupler 6,000 PSI	100
	HC/14/4/B	4 Jaw coupler 6,000 PSI	100
	<b>HYDRAULIC COUPLER - HEAVY DUTY</b>		
	HC/12/3/B	3 Jaw coupler 10,000 PSI	100
	HC/12/4/B	4 Jaw coupler 10,000 PSI	100
	<b>GREASE GUN HOSES</b>		
	GHC-12/B	Length : 300 mm (12")	30
	GHC-18/B	Length : 450 mm (18")	20
	GHC-20/B	Length : 500 mm (20")	10
	<b>GREASE GUN STEEL EXTENSIONS</b>		
	GSP/4/B	Straight, Length : 100 mm (4")	100
	GBP/6/B	Bent, Length : 150 mm (6")	100

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>GREASE CARTRIDGE - 400 GMS</b>		
	GRS/14C/CC/2G	Calcium Complex	10
	GRS/14C/PU/2G	Polyurea	10
	GRS/14C/CS/2G	Calcium sulfonate complex	10
	<b>EZEE LUBE KIT</b>		
	GAK/7	Contains 7 number of quick connect lube accessories. Ideal for use in difficult greasing job	1
	<b>GREASE FEEDERS</b>		
	GFD/PA/1/B	Polycarbonate bowl with Aluminium base. Capacity: 28 gms	1
	GFD/PA/2/B	Polycarbonate bowl with Aluminium base. Capacity: 56 gms	1
	GFD/PA/6/B	Polycarbonate bowl with Aluminium base. Capacity: 170 gms	1
	GFD/RK/1	Remote grease refill kit 3m (10') Grease hose with all fittings	1
	<b>HEAVY DUTY GREASE PUMP</b> Variable Handle Setting : pump can be set for high volume or high pressure dispensing		
	VGP/HD/10A	Capacity : 10 kg Delivers : upto 6 gm/stroke on high volume setting, Pressure : upto 6,000 PSI on high pressure setting	1
	VGP/HD/6A	Capacity : 6 kg Delivers : upto 6 gm/stroke on high volume setting, Pressure : upto 6,000 PSI on high pressure setting	1
	<b>PORTABLE GREASING SYSTEM (MANUAL)</b> Pump is operated by foot press of the spring loaded system		
	GS/5	Bucket Capacity : 5 kg Delivers : upto 1.25 gm/stroke on high volume setting, Pressure : upto 10,000 PSI on high pressure setting	1
	<b>AIR OPERATED GREASE RATIO PUMPS 50:1</b> Working pressure : 30-150 PSI Pump outlet : 1/4" BSP(F) Air inlet : 1/4" BSP(F) Air consumption : 230 LPM		
	GP1/ST/501/BSP	Pump kit with follower plate, drum cover, 84" high pressure hose & grease control valve Fits 20 to 30 kg grease drums	1
	GP2/ST/501/BSP	Pump kit with follower plate, drum cover, 84" high pressure hose & grease control valve Fits 50 to 60 kg grease drums	1
	GP3/ST4/501/BSP	Pump kit with follower plate, drum cover, 84" high pressure hose & grease control valve Fits 180 kg grease drums	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	GP3/501/BSP	Pump only (BSP thread) Fits 180 kg grease drums	1
	GP3/501/N	Pump only (NPT thread) Fits 180 kg grease drums	1
	<b>PORTABLE GREASE PUMP SYSTEM COMPLETE WITH GREASE DRUM</b> Grease Output: Upto 1.10 kg/min (NLGI 2 Grease) Max Outlet Pressure: 7500 PSI (500 BAR)		 
	BGRP/15	Portable Pump with 15 kg built-in bucket	1
	BGRP/30	Portable Pump with 30 kg built-in bucket	1
	BGRP/50	Portable Pump with 50 kg built-in bucket	1
	<b>HIGH VOLUME GREASE RATIO PUMP 50:1</b> Grease Output: 3.2 Kg per min in free flow Max. Outlet Pressure: 7500 PSI (500 BAR) Supplied complete with drum cover, rubber line, follower plate, 3 m high pressure grease hose, Z swivel & professional grease control valve		 
	GPH/1/ST/BSP	Fits 20 to 30 kg grease drums	1
	GPH/2/ST/BSP	Fits 50 to 60 kg grease drums	1
	GPH/3/ST/BSP	Fits 180 kg grease drums	1
	<b>GREASE PUMP KITS WITH HD TROLLEY</b> Ideal for use in workshops, garages, shop floors		
	TMK/GP1/A/BSP	Kit Includes • 50:1 Air Operated Grease Pump (GP1/ST/501/BSP) • Steel Drum Cover • Rubber Lined Follower Plate • 84" High pressure grease hose • Grease control valve with Z swivel • Filter - Regulator combination & lubricator with pressure gauge • Drum trolley (TRL/50) Suitable for 20-30 kg grease drums	1
	TMK/GP2/A/BSP	Kit Includes • 50:1 Air Operated Grease Pump (GP2/ST/501/BSP) • Steel Drum Cover • Rubber Lined Follower Plate • 84" High pressure grease hose • Grease control valve with Z swivel • Filter - Regulator combination & lubricator with pressure gauge • Drum trolley (TRL/50) Suitable for 50-60 kg grease drums	1
	TMK/GP3H/A/BSP	Kit Includes • 50:1 Air Operated Grease Pump (GP3/ST/501/BSP) • Steel Drum Cover • Rubber Lined Follower Plate • Heavy Duty Hose Reel - 15 m • Grease control valve with Z swivel • Filter - Regulator combination & lubricator with pressure gauge • Drum trolley (TRL/180H) Suitable for 180 kg grease drums	1
	<b>GREASE PUMP KIT WITH DRUM CART</b>		<b>NEW!</b>
	TMK1/GP3/B/BSP	Kit Includes • 50:1 Air Operated Grease Pump (GP3/ST/501/BSP) • Steel Drum Cover • Rubber Lined Follower Plate • 84" High pressure grease hose • Grease control valve with Z swivel • Drum cart (CART/400) Suitable for 180 kg grease drums	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	TMK1/GP3H/B/BSP	Kit Includes <ul style="list-style-type: none"> <li>• 50:1 Air Operated Grease Pump (GP3/ST/501/BSP)</li> <li>• Steel Drum Cover</li> <li>• Rubber Lined Follower Plate</li> <li>• Heavy Duty Hose Reel - 15 m</li> <li>• Grease control valve with Z swivel</li> <li>• Drum cart (CART/400)</li> </ul> Suitable for 180 kg grease drums	1
<b>GREASE CONTROL VALVE - PROFESSIONAL</b>			
	APG/HD/Z/1-4F/B	Grease control valve complete with Z swivel Inlet threaded : 1/4" BSPT (F) Pressure : Upto 7,500 PSI	1
<b>GREASE CONTROL VALVE - BOOSTER</b>			
	APG/Z/1-4F/B	Booster valve complete with Z swivel Inlet threaded: 1/4" BSPT (F) Pressure: Upto 7,500 PSI	1
<b>GREASE CONTROL VALVE - METERED</b>			
	APG/HD/Z/1-4F/GM/B	Meter(DGM/2/N) fitted to grease control valve Inlet: 1/4" BSPT (F) Pressure: Upto 7,500 PSI	1

## OILING EQUIPMENT

	<b>LEVER ACTION BARREL PUMP</b> For use with oil based fluids, Heating Oils, Motor Oils, Diesel & Kerosene		
	LBP/04/PT	Suitable for 50-210 litre drums Inlet : 3/4"	10
	<b>ROTARY BARREL PUMP V SERIES</b> Dual directional: Empty as well as refill container Rugged cast iron construction Recommended Use: Heating Oils, Motor Oils Lubricating Oils etc.		
	V25/3R/SPL/F	Suitable for 50-210 litre drums 3 Pc. Rigid suction tube Inlet : 1"	4
	<b>BUCKET OIL PUMPS</b> Portable pumps complete with in-built bucket for dispensing transmission, differentials & heavy oils Includes 48" PVC hose with nozzle		 
	<b>WITHOUT WHEELS</b>		
	V12	Bucket capacity : 12 litres	1
	V16	Bucket capacity : 16 litres	1
	<b>WITH WHEELS</b>		
	V12W	Bucket capacity : 12 litres	1
	V16W	Bucket capacity : 16 litres	1
	V30W	Bucket capacity : 30 litres	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>WITH WHEELS &amp; METER</b>		
	OLP/30/OM10	Bucket capacity : 30 litres With oval gear meter for optimum accuracy	1
	<b>AIR OPERATED PUMP - STAINLESS STEEL 3:1</b>		
	OP/T3/SS/BSP	3:1 Stainless steel pump For use with: 210 litre drums Delivers: Upto 14 LPM	1
	<b>AIR OPERATED OIL RATIO PUMP</b> For Use With: 210 Litre Drum		
	<b>1:1 PUMPS</b> Double acting mechanism for quick oil transfer		
	* OP/S/11B/BSP	Pressure: Upto 150 PSI Delivers: Upto 40 LPM	1
	OP/T3/11B/BSP	Pressure: Upto 150 PSI Delivers: Upto 40 LPM	1
	OPK/T3/11B/BSP	Pressure: Upto 150 PSI Delivers: Upto 40 LPM 1.5m Hydraulic hose & Oil control gun (OGN)	1
	<b>3:1 PUMPS</b>		
	* OP/S/31B/BSP	Pressure: Upto 450 PSI Delivers: Upto 14 LPM	1
	OP/T3/31B/BSP	Pressure: Upto 450 PSI Delivers: Upto 14 LPM	1
	OPK/T3/31B/BSP	Pressure: Upto 450 PSI Delivers: Upto 14 LPM 1.5m Hydraulic hose & Oil control gun (OGN)	1
	<b>5:1 PUMPS</b> Double acting mechanism for quick oil transfer		
	* OP/S/51B/BSP	Pressure: Upto 750 PSI Delivers: Upto 18 LPM	1
	OP/T3/51B/BSP	Pressure: Upto 750 PSI Delivers: Upto 18 LPM	1
	OPK/T3/51B/BSP	Pressure: Upto 750 PSI Delivers: Upto 18 LPM 1.5m Hydraulic hose & Oil control gun (OGN)	1
	<b>AIR OPERATED TRANSFER PUMP</b> Ideal for quick & safe transfer of fluids in industrial and workshop applications Suitable for use on 50-205 litre drums		
			
	ATP/1	Pump with steel suction tube	1
	ATP/1H	Pump with steel suction tube & discharge hose	1
	ATP/SS/1	Pump with stainless steel suction tube	1
ATP/SS/1H	Pump with stainless steel suction tube & discharge hose	1	

\* New Product

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>AIR OPERATED OIL RATIO PUMP-6.5:1</b> Industrial grade pneumatic oil pump designed for unmatched performance in demanding conditions For dispensing high viscosity oils (Upto SAE 240)		<b>NEW!</b>
	OPH/S-T3/61B/BSP	Flow Rate : 18 LPM Max. Air Pressure : 150 PSI Air Consumption : 250 LPM	1
	<b>OIL PUMP KITS WITH HD TROLLEY</b>		<b>NEW!</b>
	TMK/OP3/A/BSP	Kit Includes • 3:1 Air Operated Oil Ratio Pump • Digital oil control gun • 3.5 m discharge hose • Filter - Regulator combination with pressure gauge • Drum trolley (TRL/180H) Suitable for 205 liters drums	1
	TMK/OP5H/A/BSP	Kit Includes • 5:1 Air Operated Oil Ratio Pump • Digital oil control gun • 10 m Heavy Duty Hose Reel • 1.5 m feeder hose • Filter - Regulator combination & lubricator with pressure gauge • Drum trolley (TRL/180H) Suitable for 205 liters drums	1
	<b>OIL PUMP KITS WITH DRUM CART</b>		<b>NEW!</b>
	TMK1/OP3/B1/BSP	Kit Includes • 3:1 Air Operated Oil Ratio Pump • Digital oil control gun • 2 m discharge hose • Drum Cart (CART/400) Suitable for 205 liters drums	1
	TMK1/OP3H/B1/BSP	Kit Includes • 3:1 Air Operated Oil Ratio Pump • Digital oil control gun • 10 m Heavy Duty Hose Reel • 1.5 m feeder hose • Drum Cart (CART/400) Suitable for 205 liters drums	1
	TMK1/OP5/B1/BSP	Kit Includes • 5:1 Air Operated Oil Ratio Pump • Digital oil control gun • 2 m discharge hose • Drum Cart (CART/400) Suitable for 205 liters drums	1
	<b>AIR OPERATED DOUBLE DIAPHRAGM PUMPS</b>		
	AODD/1-4/FPT/N	Flow Rate : 11 LPM Suction Lift (Dry) : 5-feet Casing : Polypropylene Diaphragm : PTFE Size : 1/4"	1
	AODD/1-2/BAH/N	Flow Rate : 50 LPM Suction Lift (Dry) : 5-feet Casing : Aluminium Diaphragm : Hytrel® Size : 1/2"	1
	AODD/1-2/FPT/N	Flow Rate : 45 LPM Suction Lift (Dry) : 8-feet Casing : Polypropylene Diaphragm : PTFE Size : 1/2"	1
	AODD/1-2/FPS/N	Flow Rate : 45 LPM Suction Lift (Dry) : 8-feet Casing : Polypropylene Diaphragm : Santoprene® Size : 1/2"	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	AODD/3-4/BAH/N	Flow Rate : 110 LPM Suction Lift (Dry) : 18-feet Casing : Aluminium Diaphragm : Hytrel® Size : 3/4"	1
	AODD/3-4/BPS/N	Flow Rate : 110 LPM Suction Lift (Dry) : 18-feet Casing : Polypropylene Diaphragm : Santoprene® Size : 3/4"	1
	AODD/0-1/BAH/N	Flow Rate : 110 LPM Suction Lift (Dry) : 18-feet Casing : Aluminium Diaphragm : Hytrel® Size : 1"	1
<b>ELECTRIC OIL PUMPS</b>			
Suitable for oils (Upto SAE 90), synthetic oils, used oils, Hydraulic oils, cutting oils, Herbicides, Non-flammable oil based solvents, liquid soap etc.			
	OPM/220	Heavy Duty 220V AC pump Max Working Pressure : 65 PSI Flow rate : 16.6 LPM 3/4" Suction pipe, 3/4" x 8' Hose power cable	1
	OPM/220/HF	Heavy Duty High Flow 220V AC pump Max Working Pressure : 65 PSI Flow rate : 25 LPM 3/4" suction pipe, 3/4" x 8' hose power cable	1
	OPM/12	Heavy Duty 12V DC pump Max Working Pressure : 65 PSI Flow rate : 11.5 LPM 3/4" Suction pipe, 3/4" x 8' Hose power cable	1
<b>MECHANICAL OIL METER</b>			
	OM/10/1-2/BSP	Flow rate : 1-30 LPM Least count : 0.10 Litres Accuracy : ±1% Oval gear mechanism	1
<b>ELECTRONIC OIL METER</b>			
	OM/200/1-2/BSP	Flow rate : 1-30 LPM Least count : 0.001 Unit Accuracy : ±0.50% Oval gear mechanism	1
<b>MECHANICAL OIL CONTROL GUN</b>			
	OM/10/OGN/RM/B	Flow rate : upto 30 LPM Pressure : 1000 psi Oval gear mechanism	1
<b>ELECTRONIC OIL CONTROL GUN</b>			
	OM/200/OGN/RM/B	Flow rate: upto 30 LPM Pressure: 1000 PSI Oval gear mechanism	1
<b>ELECTRONIC PRE-SET OIL CONTROL GUN</b>			
	OM/300/PS/RA/BSP	Max. Flow Rate : 1-30 LPM Pressure : Upto 1000 PSI With steel extension & manual non-drip nozzle Oval gear mechanism	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>OIL CONTROL GUNS</b> For use with oils upto SAE 140		 
	OGN/SM/1-2R/B	With steel extension & manual non-drip nozzle	1
	OGN/SA/1-2R/B	With steel extension & automatic non-drip nozzle	1
	<b>DUAL ACTION TRANSFER GUN</b>		
	SG/20	Capacity : 350 ml Barrel : Aluminium Head : Aluminium Comes with 8' vinyle hose	20
	<b>HYDRAULIC HOSES</b>		
	HH/1.5/1-2M/3-8M/BSP	Threads: 1/2" BSP (M) × 3/8" BSP (M) Length : 1.5 Meter	1
	HH/1.5/1-2M/BSP	Threads: 1/2" BSP(M) × 1/2" BSP (M) Length : 1.5 Meter	1
	<b>SMART FUNNELS</b>		
	FNL/8	Capacity : 1.7 litres	15
	FNL/9B	Capacity : 3 litres Complete with 2" Bung For direct attachment on drums	15
	<b>PLASTIC FUNNEL SET-4 PCS.</b>		<b>NEW!</b>
	FNL/4/ST	Polypropylene construction Set of 4 Capacity : 40, 120, 245 & 430 ml	50
<b>HOSE REELS</b>			
	<b>AIR/WATER - LOW PRESSURE HOSE REELS</b>		
	HR/AW/10M/3-8/B	Max. Pressure: 300 PSI Inlet Thread: 3/8" Hose Length: 10m	1
	HR/AW/15M/3-8/B	Max. Pressure: 300 PSI Inlet Thread: 3/8" Hose Length: 15m	1
	HR/AW/10M/1-2/B	Max. Pressure: 300 PSI Inlet Thread: 1/2" Hose Length: 10m	1
	HR/AW/15M/1-2/B	Max. Pressure: 300 PSI Inlet Thread: 1/2" Hose Length: 15m	1
	<b>OIL - MEDIUM PRESSURE HOSE REELS</b>		
	HR/OL/10M/3-8/B	Max. Pressure: 2,000 PSI Inlet Thread: 3/8" Hose Length: 10m	1
	HR/OL/15M/3-8/B	Max. Pressure: 2,000 PSI Inlet Thread: 3/8" Hose Length: 15m	1
	HR/OL/10M/1-2/B	Max. Pressure: 2,000 PSI Inlet Thread: 1/2" Hose Length: 10m	1
	HR/OL/15M/1-2/B	Max. Pressure: 2,000 PSI Inlet Thread: 1/2" Hose Length: 15m	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>GREASE - HIGH PRESSURE HOSE REELS</b>		
	HR/GR/10M/1-4/B	Max. Pressure: 5,800 PSI Inlet Thread: 1/4" Hose Length: 10m	1
	HR/GR/15M/1-4/B	Max. Pressure: 5,800 PSI Inlet Thread: 1/4" Hose Length: 15m	1
	HR/GR/10M/3-8/B	Max. Pressure: 4,000 PSI Inlet Thread: 3/8" Hose Length: 10m	1
	HR/GR/15M/3-8/B	Max. Pressure: 4,000 PSI Inlet Thread: 3/8" Hose Length: 15m	1
	<b>HOSE REEL MOUNTING KIT</b>		
	SWV/HR/360	360° Heavy Duty Floor Mounting bracket	1
	SWV/HR/140	140° Heavy Duty Floor Mounting bracket	1
<b>WASTE OIL HANDLING</b>			
	<b>ELECTRIC WASTE OIL PUMPS</b> Max. Pressure: 18 PSI Suction Lift (Dry/Wet): 182 cm / 243 cm Duty Cycle: 45 min ON / 45 min OFF		
			
	EWOP/220/EU	Power Source: 220V, 50HZ AC Flow Rate: 23 LPM	1
	EWOP/12	Power Source: 12V DC Flow Rate: 17 LPM	1
	<b>WASTE OIL DRAIN - PRESSURIZED</b>		
	WOD/68A	Tank Capacity : 68 litres Max. Collection Capacity : 55 litres Draining pressure : 8 PSI	1
	<b>AIR OPERATED DOUBLE DIAPHRAGM PUMPS - V SERIES</b> Ideal for transfer of waste oil in workshops, garages etc. <b>NEW!</b>		
	AODD/25/BAH/N	 Flow Rate : 140 LPM Casing : Aluminium Diaphragm : Hytrel® Size : 1"	1
	AODD/15/BAH/N	 Flow Rate : 58 LPM Casing : Aluminium Diaphragm : Hytrel® Size : 1/2"	1
	AODD/15/BPS/N	 Flow Rate : 55 LPM Casing : Polypropylene Diaphragm : Santoprene® Size : 1/2"	1
	<b>WASTE OIL EVACUATION KITS</b> Includes: 1/2" Double Diaphragm pump , Filter Regulator combination, Two 8' PVC hoses, cam lock, Y- strainer, fittings, Pressure gauge and air hoses, Wall mounting bracket, Clamping plate & PTFE tape		
	KIT/AODD/1-2/WO/N	Diaphragm : Hytrel Flow Rate : 50 LPM Max. Particle Size : 1/32" (1 mm)	1
	KIT/AODD/0-1/WO/N	Diaphragm : Hytrel Flow Rate : 110 LPM Max. Particle Size : 1/16" (2 mm)	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>HEAVY DUTY STEEL TRUCK DRAIN</b>		
	<b>GRAVITY OIL DRAIN</b>		
	TD/68G	Reservoir Capacity: 68 litres	1
	TD/90G/BF/BL	Reservoir Capacity: 90 litres	1
	<b>OIL DRAIN WITH MANUAL ROTARY PUMP</b> Low Profile Truck Drain with Manual Rotary Pump with Baffles		
	TD/68P	Reservoir Capacity: 68 litres Pump Discharge: Upto 1 litre / 5 turns	1
	TD/90P/BF/BL	Reservoir Capacity: 90 litres Pump Discharge: Upto 1 litre / 5 turns	1
	<b>OIL DRAIN WITH 220V AC ELECTRIC PUMP</b>		
	TD/68E/220/EU	Reservoir Capacity: 68 litres Pump Discharge: Upto 23 LPM	1
	TD/90E/220/EU	Reservoir Capacity: 90 litres Pump Discharge: Upto 23 LPM	1
	<b>OIL DRAIN 12V DC ELECTRIC PUMP</b>		
	TD/68E/12	Reservoir Capacity: 68 litres Pump Discharge: Upto 17 LPM	1
TD/90E/12	Reservoir Capacity: 90 litres Pump Discharge: Upto 17 LPM	1	
	<b>PLASTIC TRUCK DRAIN</b>		
	<b>GRAVITY OIL DRAIN</b>		
	TD/17G	Reservoir Capacity: 65 litres	1
	<b>OIL DRAIN WITH MANUAL ROTARY PUMP</b>		
	TD/17P	Reservoir Capacity: 65 litres Pump Discharge: Upto 1 litre / 5 turns	1
	<b>OIL DRAIN WITH 220V AC ELECTRIC PUMP</b>		
	TD/17E/220/EU	Reservoir Capacity: 65 litres Pump Discharge: Upto 23 LPM	1
<b>OIL DRAIN 12V DC ELECTRIC PUMP</b>			
TD/17E/12	Reservoir Capacity: 65 litres Pump Discharge: Upto 17 LPM	1	
<b>FUEL HANDLING EQUIPMENT</b>			
	<b>EXPLOSION PROOF HIGH FLOW ELECTRIC FUEL PUMPS</b> 12V DC Explosion Proof Motor Duty Cycle : 30 minutes on/30 minutes off Recommended Use : Petrol, Diesel, E-15 Fuel, Kerosene, Bio Diesel		 
	FPM/12/HF/D	Pump complete with suction tube, bung nut, discharge hose, power cable & manual nozzle	1
	FPM/12/HF/FMT/D	Pump complete with suction tube, bung nut, discharge hose, power cable, manual nozzle, Fuel filter & Fuel Filter	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>EXPLOSION PROOF ELECTRIC FUEL PUMPS</b> Duty Cycle : 30 minutes on/30 minutes off Recommended Use : Petrol, Diesel, E-15 Fuel, Kerosene, Bio Diesel		 
	FPM/12/D	12V DC Pump Flow Rate : Upto 57 LPM*	1
	FPM/24/D	24V DC Pump Flow Rate : Upto 57 LPM*	1
	FPM/12/MT/D	12V DC Pump with mechanical fuel meter	1
	FPM/12/FMT/D	12V DC Pump with mechanical fuel meter & fuel filter	1
	* FPM/12/FMT/2000/D	12V DC Pump with Digital fuel meter & fuel filter	1
	* FPM/220/D	220V AC pump with suction tube, bung nut, power cable, discharge hose & manual nozzle	1
	<b>CONTINUOUS DUTY ELECTRIC DIESEL PUMP</b> With thermal overload protection Suitable for stationary applicaitons Recommended Use : Diesel & Kerosene		
	CDP/220UR/EU	1/2 HP, 220V AC, 50 Hz., Power cord included Flow rate : Upto 56 LPM	1
	* CDP/220/80/EU	3/4 HP, 220V AC, 2M Power cord included Flow rate : Upto 80 LPM	1
	<b>MINI BOWSER DIESEL PUMPS REFILLING SYSTEM</b> Recommended Use : Diesel & Kerosene		 
	CBN/220EU/L/A/D	Complete system for diesel refilling application. Includes: <ul style="list-style-type: none"> <li>• Continuous Duty Electric Fuel Pump: 1/2 HP 220V AC, 50 Hz</li> <li>• Mechanical Diesel Meter</li> <li>• Fuel Control Nozzle – Automatic</li> <li>• Fuel Hose</li> <li>• Nozzle Holder</li> <li>• Hose Hangar</li> </ul> Flow rate: Upto 44 LPM	1
	<b>ELECTRIC DIESEL PUMP BASE MOUNT</b> Recommended Use : Diesel & Kerosene		
	EDP/12M/ST	12V DC pump assembly with manual nozzle,	1
	EDP/24M/ST	24V DC Pump assembly with manual nozzle	1
	<b>ELECTRIC DIESEL PUMP - HEAVY DUTY</b> Recommended Use : Diesel & Kerosene		<b>NEW!</b> 
	EDP/HD/24M/ST	24V DC portable Heavy Duty Diesel Transfer Pump	1
	<b>FUEL DISPENSER</b> The Diesel dispensing system stands as an indispensable solution, revolutionizing the way fuel is distributed to vehicles and machinery.		<b>NEW!</b>
	FD/60/12/D	Voltage: 12V Inlet: 1" BSP Outlet: 1" BSP	1

\* New Product

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>INDUSTRIAL ROTARY FUEL PUMPS</b> Recommended Use : Petroleum based fluids, Diesel, Petrol & Kerosene		
	RBP/3V	Pump with steel discharge spout	1
	RBP/3V/H	Pump with 8' anti-static fuel hose, non-sparking aluminium nozzle & nozzle holder	1
	<b>ROTARY BOOSTER PUMP 3:1</b> Geared pump : For every turn of the handle the rotor turns 3 times Recommended Use : Diesel, Petrol & Kerosene		
	RB/3H	Pump with 1.8 m discharge hose, metal nozzle, spring & hose clamp  Empties a 210 litre drum in 3 minutes	1
	<b>MECHANICAL DIESEL METER</b> Recommended Use : Diesel, Biodiesel, Oils Nutating disc mechanism		 
	FM/10/0-1/BSP	Inlet/Outlet : 1" BSP(F) Least count : 0.10 liters Accuracy : ±1%	1
	<b>DIGITAL FUEL METER HEAVY DUTY</b> Recommended Use : Diesel, Petrol, Biodiesel, Oils, Windshield Fluids and Water Turbine mechanism		 
	FM/20/0-1/BSP	Inlet/outlet : 1" BSP (M) x 1" BSP (F) Least count : 0.001 units Accuracy : ±1%	1
	<b>DIGITAL OVAL GEAR FUEL METER</b> Recommended Use : Diesel, Oils, Antifreeze		 
	FM/25/3-4/BSP	Inlet/outlet: 3/4" BSP (F) Least count: 0.001 units Accuracy: ±1%	1
	FM/25/0-1/BSP	Inlet/outlet: 1" BSP (F) Least count: 0.001 units Accuracy: ±1%	1
	<b>DIGITAL FUEL METER PROFESSIONAL</b> Recommended Use : Diesel, Gasoline, Bio Diesel Turbine mechanism		 
	FM/2000/0-1/BSP	Inlet/outlet: 1" BSP (F) Least count: 0.001 units Accuracy: ±1%	1
	<b>FUEL CONTROL NOZZLES - MANUAL</b> Recommended Use : Diesel, Petrol & Kerosene		 
	FCN/S/3-4/3-4/N	Inlet Thread : 3/4" NPT (F) Flow Rate : 57 LPM	1
	FCN/S/0-1/0-1/N	Inlet Thread : 1" NPT (F) Flow Rate : 75 LPM	1
	<b>FUEL CONTROL NOZZLES - AUTOMATIC</b> Spout Type: Curved with spring Recommended Use : Diesel, Petrol & Kerosene		 
	FCNA/3-4A/N	Inlet Thread : 3/4" NPT (F) Flow Rate : 60 LPM	1
	FCNA/0-1/N	Inlet thread : 1" NPT (F) Flow Rate : 110 LPM	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>FUEL CONTROL NOZZLES - METERED</b> Comes with digital fuel meter (FM/20) Recommended Use : Diesel, Petrol		 
	FM/20/FCN/3-4/N	Inlet Thread : 3/4" NPT (F) Flow Rate : 75 LPM	1
	FM/20/FCN/0-1/N	Inlet thread : 1" NPT (F) Flow Rate : 75 LPM	1
	<b>DUAL PLANE FUEL NOZZLE SWIVELS</b> Provides a full 360° rotation for free movement facilitating flexibility to refuel vehicles from virtually any direction.		
	SWV/2P/3-4/N	Thread : 3/4" NPT (F) x 3/4" NPT (M)	1
	SWV/2P/0-1/N	Thread : 1" NPT (F) x 1" NPT (M)	1
	<b>FUEL DISPENSING KIT</b> 3m Fuel Hose fitted with manual fuel control nozzle		
	FDK/3/3-4/N	Hose inner diameter : 3/4"	1
	FDK/3/0-1/N	Hose inner diameter : 1"	1
	<b>ANTI-STATIC FUEL HOSE</b> 3.6m Fuel Hose complete with end connections		
	ZSA/HOS/FPM/12	Hose inner diameter : 3/4"	1
	ZSA/HOS/FPM/12/HF	Hose inner diameter : 1"	1
	<b>FILTER WRENCH</b>		
	FW/FFL-02	Used for easy removal of filter bowl without damage	10
	<b>HIGH FLOW 10 MICRON FUEL FILTER</b> Recommended Use : Diesel, Petrol, Fuel Oil, Ethyl and Isopropyl Alcohol		
	FFL-01/B	Fuel filter, Threaded : 1" BSP (F)	10
	* FFL/01/3-4/N	Fuel filter, Threaded : 3/4" BSP (F)	10
	<b>REPLACEMENT FILTER ELEMENT</b>		
	FF/FFL/10-ST	Fuel filter element : 10μ	10
	FF/FFL/10-WB/ST	Water block fuel filter element : 10μ	10
	<b>FUEL FILTER SPIN - ON CARTRIDGE STYLE</b> Recommended Use : Diesel & Petrol		 
	FFS/10/BSP	Inlet/Outlet : 1" BSP(F) Fuel filter : 10μ	10
	FFS/10WB/BSP	Inlet/Outlet : 1" BSP(F) Fuel filter : 10μ water block	10
	<b>REPLACEMENT CARTRIDGE</b>		
	FF/FFS/10	10μ Filter element	10
	FF/FFS/10-WB	10μ Filter water block	10
	<b>DEF HANDLING EQUIPMENT</b>		
	<b>DEF DIGITAL TURBINE METER</b>		  
	WM/20/0-1/BSP	Inlet/outlet : 1" BSP (F) Least Count/ Resolution : 0.001 units Accuracy : ± 1%	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>ELECTRIC DEF TRANSFER PUMPS</b>		  
	DEFP/12	Power Source : 12V DC Inlet / Outlet : 3/4" Hose Barb Duty Cycle : 30 minutes ON / 30 minutes OFF	1
	DEFP/220	Power Source : 220V AC, 50 Hz. Inlet / Outlet : 3/4" Hose Barb Duty Cycle: 30 minutes ON / 30 minutes OFF	1

### DEF TRANSFER SYSTEMS

	<b>TOTE TRANSFER KITS</b>		
	KIT/IBC/DEF/1/EU	Includes 1. Stainless Steel Tote Mounting Plate 2. Electric DEF Pump 3. DEF Control Nozzle - Manual with Swivel 4. Inlet Hose 5. Discharge Hose 6. Suction Hose 7. Connecting Hardware	1
	KIT/IBC/DEF/2/EU/D	Includes 1. Stainless Steel Tote Mounting Plate 2. Electric DEF Pump 3. DEF Control Nozzle - Manual with Swivel 4. Bottom Connecting Adaptors 5. Inlet Hose 6. Discharge Hose 7. Connecting Hardware	1
	KIT/IBC/DEF/3/EU/D	Includes 1. Stainless Steel Tote Mounting Plate 2. Electric DEF Pump 3. DEF Control Nozzle - Automatic with Swivel 4. Bottom Connecting Adaptors 5. Inlet Hose 6. Discharge Hose 7. Connecting Hardware	1
	KIT/IBC/DEF/4/EU/D	Includes 1. Stainless Steel Tote Mounting Plate 2. Electric DEF Pump 3. DEF Digital Turbine Meter 4. DEF Control Nozzle - Automatic with Swivel 5. Bottom Connecting Adaptors 6. Inlet Hose 7. Discharge Hose 8. Connecting Hardware	1
	* KIT/IBC/DEF/5/EU/D	Includes 1. Stainless Steel Tote Mounting Plate 2. Electric DEF Pump 3. DEF Digital Turbine Meter 4. DEF Control Nozzle - Manual with Swivel 5. Bottom Connecting Adaptors 6. Inlet Hose 7. Discharge Hose 8. Connecting Hardware	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>DRUM TRANSFER KITS</b>		
	KIT/DRM/DEF/1/EU	Includes 1. Stainless Steel Tote Mounting Plate 2. Electric DEF Pump 3. DEF Control Nozzle Manual with Swivel 4. Inlet Hose 5. Discharge Hose 6. Suction Hose 7. Connecting Hardware	1
	KIT/DRM/DEF/2/EU/D	Includes 1. Stainless Steel Tote Mounting Plate 2. Electric DEF Pump 3. DEF Control Nozzle Manual with Swivel 4. Connecting Adaptors 5. Inlet Hose 6. Drum Bung Convertor 7. Discharge Hose 8. Connecting Hardwar	1
	KIT/DRM/DEF/3/EU/D	Includes 1. Stainless Steel Tote Mounting Plate 2. Electric DEF Pump 3. DEF Control Nozzle - Automatic with Swivel 4. Connecting Adaptors 5. Inlet Hose 6. Drum Bung Convertor 7. Discharge Hose 8. Connecting Hardware	1
	KIT/DRM/DEF/4/EU/D	Includes 1. Stainless Steel Tote Mounting Plate 2. Electric DEF Pump 3. DEF Digital Turbine Meter 4. DEF Control Nozzle - Automatic with Swivel 5. Connecting Adaptors 6. Inlet Hose 7. Drum Bung Convertor 8. Discharge Hose 9. Connecting Hardware	1
	<b>DEF DISPENSER</b> A DEF dispensing system is a crucial component in the world of modern diesel engines		<b>NEW!</b>  40 LPM
	AD/40/220/D	Voltage: 220V Inlet: 1" BSP Outlet: 3/4" BSP	1
	<b>DEF CONTROL NOZZLE - MANUAL</b> Recommended Use: Diesel Exhaust Fluid & Urea		 
	FCN/NY/HB/3-4	Inlet: 3/4" Hose Barb	1
	<b>DEF CONTROL NOZZLE - AUTOMATIC</b> Recommended Use: Diesel Exhaust Fluid & Urea		<b>NEW!</b>  
	FCNA/SS/HB/3-4	Inlet: 3/4" Hose Barb	1

	CAT NR.	DESCRIPTION / SIZE	MOQ.
<b>SPECIALITY PUMPS</b>			
	<b>DRY CELL DEF PUMP</b> Recommended Use : Petrol, Diesel, Kerosene, DEF, Antifreeze, Windshield Fluid, mild detergents, agricultural chemicals, Herbicides Pesticides & Water		<b>NEW!</b> 
	BOP/50	Self priming pump with 3V DC motor Total Length: 674 mm Suction tube Length: 467 mm Works on 2 x 'D' Size alkaline battery (Not included with pump)	40
	<b>BATTERY TRANSFER PUMP</b> Recommended Use : Diesel, Kerosene, Light oils, DEF, Water, Antifreeze, Windshield fluid, Mild detergents, Agricultural chemicals etc.		<b>NEW!</b> 
	BOP/5A	Suitable for use 20 litres pails Suction tube length : 385mm Works on 2 x 'D' Size alkaline battery (Not included with pump)	40
	<b>RECHARGEABLE DEF PUMP</b> Recommended Use : Diesel, Kerosene, Light oils, DEF, Water, Antifreeze, Windshield fluid, Mild detergents, Agricultural chemicals etc.		<b>NEW!</b> 
	BOP/60	2900 mAh Lithium ion battery. Rechargeable via USB Cable (cable included) Telescopic suction tube Suitable for 20-50 litre drums	10
	<b>ELECTRIC DRUM / IBC PUMPS</b> Duty Cycle : 15 minutes ON / 15 minutes OFF Rechargeable Battery : 18.5V, 1.3Ah Li-Ion Rechargeable Battery AC Dual Voltage Adaptor		<b>NEW!</b> 
	EDR/55T/AC/EU	Telescopic suction tube Suitable for use with 210 litre drums or 1000-1250 litre IBC / Totes Built-in 2" bung adaptor Complete with 2m (6.6') hose & manual dispensing nozzle with 3/4" (19 mm) OD Stainless Steel Spout	4
	<b>ROTARY DRUM PUMP - STAINLESS STEEL</b> Recommended Use : Water based media, antifreeze, acids, chemicals, all petroleum based products, lacquer, thinner, urea, DEF 3 pc suction tube		<b>NEW!</b> 
	GNB/SS/25/3R/SPL	Suitable for use 50 to 205 litres drums	4
	<b>NYLON CHEMICAL PUMP</b> Recommended Use : Lacquer, Thinners, Detergents, Glycerine, Water, Weed Killer, Brake Kleen, Mild Acids & Petroleum Based Media		
	CMP/12	Suitable for use on 50-210 litre drums	10

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>PLASTIC ROTARY PUMP</b> Rotary Action Polypropylene pump with viton rubber seal & stainless steel hardware Recommended Use : Water based media, acids, chemicals, detergents, benzene, glycerine etc.		
	PRP/01	Suitable for use on 50-210 litre drums	6
	<b>PLASTIC LEVER PUMP</b> Recommended Use : Water Based Media, Detergents, Soaps, Windshield Washer, Lubricants, Agricultural Chemicals, Herbicides & Pesticides		
	PLP/02	Suitable for use on 50-210 litre drums	1
	<b>PLASTIC LEVER PUMP - VALUE</b> Recommended Use : Petroleum-based non-corrosive liquids, Diesel, Kerosene Light oils, Low viscosity lubricants, Acetone, Antifreeze, Ammonium Hydroxide, Glycerine, Alcohols, Water based chemicals, Weaker acids, Mild solvents and Alkaline solutions.		<b>NEW!</b> 
	PLP/20	Suitable for use on 50-210 litre drums Variable handle setting	10
<b>DRUM HANDLING</b>			
	<b>DRUM DOLLY - 4 WHEEL</b>		
	BDL/140S	For convenient movement of 180 kg/210 litre drums Cast iron castors	2
	<b>LOW PROFILE DRUM TROLLEY</b>		
	TRL/55	For convenient movement of 180 kg/210 litre drums	1
	<b>DRUM TROLLEYS</b>		
	TRL/50	For convenient movement of 50 kg/60 litre drums	1
	* TRL/180H		
		For convenient movement of 180 kg/210 litre drums Includes base for mounting hose reel	1
	<b>DRUM CRADLE</b>		
	DRC/135	Tips, rotates, moves & stores 400 lbs. / 180kg / 210 litre / 55 gal. drums  Maximum load 600 lbs. / 273 kgs	3

	CAT NR.	DESCRIPTION / SIZE	MOQ.
	<b>HEAVY DUTY DRUM CART</b> Suitable For : For 180 kg / 210 litre drums Rear base for mounting hose reel		<b>NEW!</b>
	CART/400	Phenolic Wheels	1
	CART/400P	Pneumatic Wheels	1
<b>AIR LINE ACCESSORIES</b>			
	<b>AIR BLOW GUN - STANDARD</b>		
	ABG/1/1-4F/BSP	Air blow gun (Nylon) with Plastic Tip	10
	ABG/3/1-4F/BSP	Air blow gun (Nylon) with 4-1/2" (114 mm) long SS nozzle	10
	<b>AIR BLOW GUN - PROFESSIONAL</b>		
	ABG/10/1-4F/BSP	Comes with 4-1/2" steel tip	10
	<b>FILTER REGULATOR COMBINATION</b>		
	FRC136134-S/GB	Type : Miniature Inlet/Outlet Port Size : 1/4" BSP Max. Flow Rate : 550 LPM	1
	FRC156334-S/GB	Type : Standard Inlet/Outlet Port Size : 1/2" BSP Max. Flow Rate : 3000 LPM	1
	<b>FILTER REGULATOR &amp; LUBRICATOR - 2PCS</b>		
	FRCLM136134-S/WG	Type : Miniature Inlet/Outlet Port Size : 1/4" BSP Max. Flow Rate : 500 LPM	1
	FRCLM156334-S/WG	Type : Miniature Inlet/Outlet Port Size : 1/2" BSP Max. Flow Rate : 2800 LPM	1
	<b>DIGITAL PRESSURE GAUGES</b>		  
	DPG/L/1-8/B	Threaded 1/8" BSPT (M)	10
	DPG/L/1-4/B	Threaded 1/4" BSPT (M)	10
	<b>TYRE INFLATOR GAUGE FOR CARS</b>		
	TIG/D/12/BSP	12" (300 mm) flexible hose with straight chuck Max Pressure : Upto 50 PSI Digital Gauge	1
	<b>TYRE INFLATOR GAUGE FOR TRUCKS</b>		
	TIG/D/24D/BSP	24" (600 mm) flexible hose with dual chuck Max Pressure : 230 PSI, Digital Gauge	1









**Groz Engineering Tools Pvt. Ltd.**  
**Groz Net Industries**

**Manufacturing Facilities**  
Gurugram, Noida, Karoli & Chennai

The GROZ name, GROZ logo and the  mark are trademarks of Groz Engineering Tools Pvt. Ltd., India

**PROUDLY INDIAN**