

LOGREASE 1

DESCRIPTION

LOGREASE 1 is a multipurpose extreme pressure grease having a high stability to mechanical shear, along with a good resistance to water. LOGREASE 1 is flexible to low temperatures and has a very good resistance to shocks and high loads. LOGREASE 1 has effective anti-corrosion and anti-oxidation additives package.

TYPICAL APPLICATIONS

LOGREASE 1 is well adapted for the lubrication of all types of bearings and articulation which may be submitted to several conditions. LOGREASE 1 is well suited for centralized lubrication systems that are designed to use NLGI grade 1 grease.

TECHNICAL CHARACTERISTICS

PROPERTIES	VALUES	UNITS	STANDARDS
Colour	amber		(visual)
Thickener	lithium		
Base oil	mineral		
Kinematic viscosity (40°C)	130	mm ² /s	ISO 3104
Kinematic viscosity (100°C)	11	mm ² /s	ISO 3104
Consistency	1	rank	NLGI
Drop point	190	°C	ISO 6299
Worked penetration	310/340	X0.1 mm	ISO 2137
4 Balls weld test	2850	N	ASTM D 2596
Temperature range	-30 to +130	°C	

All information contained here is given in good faith. It is provided without warranty, express or implied, and is subjected to change without notice.